## LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK AND GOLD 840 (12W)

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

| Index:                             | 780295    |
|------------------------------------|-----------|
| Ingress protection:                | IP20      |
| Rated power of the luminaire [W]*: | 12        |
| Luminous flux [lm]*:               | 1020      |
| Colour temperature [K]:            | 4000      |
| Colour rendering index:            | <80       |
| Electrical protection class:       | II        |
| Energy efficiency class:           | Е         |
| Material of the body:              | aluminium |
| Colour of the body:                | black     |
|                                    |           |

#### **CHARACTERISTICS**

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra  $\geq$  80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

#### **APPLICATION**

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



# LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK AND GOLD 840 (12W)

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

| Rated power of the luminaire [W]:  EAN: 5905963780295  Colour temperature [K]: 4000  Light source: LED  Luminous flux [Im]: 1020  Supply voltage [V]: 230  Frequency [Hz]: 50-60  Luminous efficacy [Im/W]: 85  Electrical protection class: II  Energy efficiency class: E  Beam angle [°]: 20  Colour rendering index: <80  Light colour: neutralna biel  Exchangeable source: yes  Optics material: aluminium  Colour of the body: black | Index:                            | 780295        |
|---|-----------------------------------|---------------|
| EAN:  Colour temperature [K]:  Light source:  Luminous flux [Im]:  Supply voltage [V]:  Frequency [Hz]:  Luminous efficacy [Im/W]:  Electrical protection class:  Energy efficiency class:  Beam angle [°]:  Colour rendering index:  Light colour:  Exchangeable source:  Optics material:  4000  1020  230  50-60  85  B1  E  E  E  E  E  E  E  E  E  E  E  E  E  |                                   | 15525         |
| Colour temperature [K]: 4000  Light source: LED  Luminous flux [Im]: 1020  Supply voltage [V]: 230  Frequency [Hz]: 50-60  Luminous efficacy [Im/W]: 85  Electrical protection class: II  Energy efficiency class: E  Beam angle [°]: 20  Colour rendering index: <80  Light colour: neutralna biel  Exchangeable source: yes  Optics material: aluminium   | Rated power of the luminaire [W]: | 12            |
| Light source: Luminous flux [lm]:  Supply voltage [V]:  Frequency [Hz]:  Luminous efficacy [lm/W]:  Electrical protection class:  Energy efficiency class:  Beam angle [°]:  Colour rendering index:  Light colour:  Exchangeable source:  Optics material:   | EAN:                              | 5905963780295 |
| Luminous flux [lm]:  Supply voltage [V]:  Frequency [Hz]:  Luminous efficacy [lm/W]:  Electrical protection class:  Energy efficiency class:  Beam angle [°]:  Colour rendering index:  Light colour:  Exchangeable source:  Optics material:  1020  85  E  20  <80  Light colour:  peutralna biel  yes  Aluminium  | Colour temperature [K]:           | 4000          |
| Supply voltage [V]:  Frequency [Hz]:  Luminous efficacy [Im/W]:  Electrical protection class:  Energy efficiency class:  Beam angle [°]:  Colour rendering index:  Light colour:  Exchangeable source:  Optics material:  230  85  85  82  85  86  87  88  80  80  80  80  80  80  80  80   | Light source:                     | LED           |
| Frequency [Hz]: 50-60  Luminous efficacy [Im/W]: 85  Electrical protection class: II  Energy efficiency class: E  Beam angle [°]: 20  Colour rendering index: <80  Light colour: neutralna biel  Exchangeable source: yes  Optics material: aluminium   | Luminous flux [Im]:               | 1020          |
| Luminous efficacy [lm/W]:  Electrical protection class:  Energy efficiency class:  Beam angle [°]:  Colour rendering index:  Light colour:  Exchangeable source:  Optics material:  85   80   | Supply voltage [V]:               | 230           |
| Electrical protection class:  Energy efficiency class:  Beam angle [°]:  Colour rendering index:  Light colour:  Exchangeable source:  Optics material:  Il  E  20  Colour rendering index:   | Frequency [Hz]:                   | 50-60         |
| Energy efficiency class:  Beam angle [°]:  Colour rendering index:  Light colour:  Exchangeable source:  Optics material:  Energy efficiency class:  E 20   |                                   |               |

| Optics:                        | reflector               |
|--------------------------------|-------------------------|
| Material of the body:          | aluminium               |
| Ring colour:                   | gold                    |
| Wire type:                     | czerwony oplot          |
| Ring material:                 | aluminium               |
| Control:                       | ON/OFF                  |
| Dimensions (H/W/T/S) [mm]:     | fi=60 L=170 H=1500      |
| Mounting dimensions [mm]:      | szynoprzewód            |
| Ingress protection:            | IP20                    |
| Mounting version:              | suspended from trunking |
| Cable length [m]:              | 1.50                    |
| Dimensions of single box [mm]: | fi=90mm L=335mm         |
| LED lifespan L90B10 [h]:       | 60000                   |
| CE certificate:                | <u>51/2025</u>          |
| Manual:                        | Download PDF            |

Card creation date: 23 May 2025





Page 2/2