# LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK AND GOLD 840 (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 780301 |
| **Rated power of the luminaire [W]*:** | 12 |
| **Luminous flux [lm]*:** | 1120 |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **Beam angle [°]:** | 40 |
| **Material of the body:** | aluminium |
| **Colour of the body:** | black |
| **Ring colour:** | gold |
| **Dimensions (H/W/T/S) [mm]:** | fi=60 L=170 H=1500 |

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra ≥ 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Luminaire is used in spaces such as:
- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK AND GOLD 840 (12W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 780301 |
| **EAN:** | 5905963780301 |
| **Category type:** | decorative fixtures |
| **Category of application:** | architectural, office lighting, commercial facilities |
| **Light source:** | LED |
| **Rated power of the luminaire [W]:** | 12 |
| **Luminous flux [lm]:** | 1120 |
| **Supply voltage [V]:** | 230 |
| **Frequency [Hz]:** | 50-60 |
| **Luminous efficacy [lm/W]:** | 91 |
| **Energy efficiency class:** | E |
| **Electrical protection class:** | II |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **LED lifespan L90B10 [h]:** | 60000 |
| **Working temperature [°C]:** | from 0 to +35 |
| **Beam angle [°]:** | 40 |
| **Exchangeable source:** | yes |
| **Optics:** | reflector |
| **Optics material:** | aluminium |
| **Material of the body:** | aluminium |

| | |
|---|---|
| **Colour of the body:** | black |
| **Ring material:** | aluminium |
| **Ring colour:** | gold |
| **Dimensions (H/W/T/S) [mm]:** | fi=60 L=170 H=1500 |
| **Mounting dimensions [mm]:** | szynoprzewód |
| **Ingress protection:** | IP20 |
| **Mounting version:** | suspended from trunking |
| **Control:** | ON/OFF |
| **Dimensions of single box [mm]:** | fi=90mm L=335mm |
| **Number on the palette [pcs]:** | 416 |
| **Net weight [kg]:** | 0.600 |
| **Gross weight [kg]:** | 0.700 |
| **Wire type:** | red braid |
| **Cable length [m]:** | 1.50 |
| **Photobiological safety:** | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| **Warranty [years]:** | 5 |
| **CE certificate:** | 01/2026 |
| **Manual:** | Download PDF |
| **ISO Certificates:** | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| **Plik LDT:** | Download |

Card creation date: 21 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 01/2026

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl