

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK 840 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780349
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1170
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK 840 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780349
EAN:	5905963780349
Light source:	LED
Rated power of the luminaire [W]:	12
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous flux [lm]:	1170
Luminous efficacy [lm/W]:	95
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	80
Beam angle [°]:	70
Light colour:	neutralna biel
Exchangeable source:	yes
Optics material:	aluminium
Optics:	reflector
Material of the body:	aluminium
Colour of the body:	black

Ring material:	aluminium
Ring colour:	black
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	szynoprzewód
Ingress protection:	IP20
Mounting version:	suspended from trunking
DIMM DALI:	yes
Control:	yes
Wire type:	black braid
Cable length [m]:	1.50
Number on the palette [pcs]:	312
Dimensions of single box [mm]:	fi=90mm L=400mm
Net weight [kg]:	0.600
Gross weight [kg]:	0.700
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	51/2025
Manual:	Download PDF

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl