

# LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 DALI (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	780363
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1120
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Beam angle [°]:	40
Material of the body:	aluminium
Colour of the body:	white
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ( $Ra \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 DALI (12W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	780363	<b>Ring material:</b>	aluminium
<b>EAN:</b>	5905963780363	<b>Ring colour:</b>	white
<b>Category type:</b>	decorative fixtures	<b>Dimensions (H/W/T/S) [mm]:</b>	fi=60 L=170 H=1500
<b>Category of application:</b>	architectural, office lighting, commercial facilities	<b>Mounting dimensions [mm]:</b>	szynoprzewód
<b>Light source:</b>	LED	<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]:</b>	12	<b>Mounting version:</b>	suspended from trunking
<b>Luminous flux [lm]:</b>	1120	<b>DIMM DALI:</b>	yes
<b>Supply voltage [V]:</b>	230	<b>Dimensions of single box [mm]:</b>	fi=90mm L=400mm
<b>Frequency [Hz]:</b>	50-60	<b>Number on the palette [pcs]:</b>	312
<b>Luminous efficacy [lm/W]:</b>	91	<b>Net weight [kg]:</b>	0.600
<b>Energy efficiency class:</b>	E	<b>Gross weight [kg]:</b>	0.700
<b>Electrical protection class:</b>	II	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Colour temperature [K]:</b>	4000	<b>Warranty [years]:</b>	5
<b>Color rendering index (Ra) &gt;:</b>	80	<b>CE certificate:</b>	<a href="#">01/2026</a>
<b>LED lifespan L90B10 [h]:</b>	60000	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Beam angle [°]:</b>	40	<b>Nominal power [W]:</b>	13
<b>Exchangeable source:</b>	yes	<b>Control:</b>	yes
<b>Optics:</b>	reflector	<b>Wire type:</b>	white braid
<b>Optics material:</b>	aluminium	<b>Cable length [m]:</b>	1.50
<b>Material of the body:</b>	aluminium	<b>Plik LDT:</b>	<a href="#">Download</a>
<b>Colour of the body:</b>	white		

Card creation date: 21 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 01/2026