

LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780363
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1120
Colour temperature [K]:	4000
Colour rendering index:	<80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780363
Rated power of the luminaire [W]:	12
EAN:	5905963780363
Colour temperature [K]:	4000
Light source:	LED
Luminous flux [lm]:	1120
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	91
Electrical protection class:	II
Energy efficiency class:	E
Beam angle [°]:	40
Colour rendering index:	<80
Light colour:	neutralna biel
Exchangeable source:	yes
Optics material:	aluminium
Colour of the body:	white

Optics:	reflector
Material of the body:	aluminium
Ring colour:	white
Wire type:	biały oplot
Ring material:	aluminium
Control:	yes
DIMM DALI:	yes
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	szynoprzewód
Ingress protection:	IP20
Mounting version:	suspended from trunking
Cable length [m]:	1.50
Dimensions of single box [mm]:	fi=90mm L=400mm
LED lifespan L90B10 [h]:	60000
CE certificate:	51/2025
Manual:	Download PDF