

# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 DALI (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	780370
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1170
Colour temperature [K]:	4000
Colour rendering index:	<80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ( $Ra \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 DALI (12W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	780370	Material of the body:	aluminium
EAN:	5905963780370	Colour of the body:	white
Light source:	LED	Ring material:	aluminium
Rated power of the luminaire [W]:	12	Ring colour:	white
Supply voltage [V]:	230	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Frequency [Hz]:	50-60	Mounting dimensions [mm]:	szynoprzewód
Luminous flux [lm]:	1170	Ingress protection:	IP20
Luminous efficacy [lm/W]:	95	Mounting version:	suspended from trunking
Energy efficiency class:	E	DIMM DALI:	yes
Electrical protection class:	II	Control:	yes
Colour temperature [K]:	4000	Wire type:	white braid
Colour rendering index:	<80	Cable length [m]:	1.50
Beam angle [°]:	70	Dimensions of single box [mm]:	fi=90mm L=400mm
Light colour:	neutralna biel	LED lifespan L90B10 [h]:	60000
Exchangeable source:	yes	CE certificate:	<a href="#">51/2025</a>
Optics material:	aluminium	Manual:	<a href="#">Download PDF</a>
Optics:	reflector		

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)