

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20

SUSPENDED TRACK SILVER 840 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780387
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1020
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Beam angle [°]:	20
Material of the body:	aluminium
Colour of the body:	silver
Ring colour:	silver
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20

SUSPENDED TRACK SILVER 840 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780387	Colour of the body:	silver
EAN:	5905963780387	Ring material:	aluminium
Category type:	decorative fixtures	Ring colour:	silver
Category of application:	architectural, office lighting, commercial facilities	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Light source:	LED	Mounting dimensions [mm]:	szynoprzewód
Rated power of the luminaire [W]:	12	Ingress protection:	IP20
Luminous flux [lm]:	1020	Mounting version:	suspended from trunking
Supply voltage [V]:	230	Control:	yes
Frequency [Hz]:	50-60	DIMM DALI:	yes
Luminous efficacy [lm/W]:	85	Dimensions of single box [mm]:	fi=90mm L=400mm
Energy efficiency class:	E	Number on the palette [pcs]:	312
Electrical protection class:	II	Net weight [kg]:	0.600
Colour temperature [K]:	4000	Gross weight [kg]:	0.700
Color rendering index (Ra) >:	80	Wire type:	black braid
LED lifespan L90B10 [h]:	60000	Cable length [m]:	1.50
Working temperature [°C]:	from 0 to +35	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	20	Warranty [years]:	5
Exchangeable source:	yes	CE certificate:	01/2026
Optics:	reflector	Manual:	Download PDF
Optics material:	aluminium	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Material of the body:	aluminium	Plik LDT:	Download