

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK SILVER 840 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|-----------|
| Index: | 780400 |
| Ingress protection: | IP20 |
| Rated power of the luminaire [W]*: | 12 |
| Luminous flux [lm]*: | 1170 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| Electrical protection class: | II |
| Energy efficiency class: | E |
| Material of the body: | aluminium |
| Colour of the body: | silver |

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK SILVER 840 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | |
|-----------------------------------|----------------|
| Index: | 780400 |
| EAN: | 5905963780400 |
| Light source: | LED |
| Rated power of the luminaire [W]: | 12 |
| Supply voltage [V]: | 230 |
| Frequency [Hz]: | 50-60 |
| Luminous flux [lm]: | 1170 |
| Luminous efficacy [lm/W]: | 95 |
| Energy efficiency class: | E |
| Electrical protection class: | II |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| Beam angle [°]: | 70 |
| Light colour: | neutralna biel |
| Exchangeable source: | yes |
| Optics material: | aluminium |
| Optics: | reflector |
| Material of the body: | aluminium |
| Colour of the body: | silver |

| | |
|--------------------------------|------------------------------|
| Ring material: | aluminium |
| Ring colour: | silver |
| Dimensions (H/W/T/S) [mm]: | fi=60 L=170 H=1500 |
| Mounting dimensions [mm]: | szynoprzewód |
| Ingress protection: | IP20 |
| Mounting version: | suspended from trunking |
| DIMM DALI: | yes |
| Control: | yes |
| Wire type: | black braid |
| Cable length [m]: | 1.50 |
| Number on the palette [pcs]: | 312 |
| Dimensions of single box [mm]: | fi=90mm L=400mm |
| Net weight [kg]: | 0.600 |
| Gross weight [kg]: | 0.700 |
| LED lifespan L90B10 [h]: | 60000 |
| Warranty [years]: | 5 |
| CE certificate: | 51/2025 |
| Manual: | Download PDF |

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl