**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index: 608452

Luminous flux of the luminaire [Im] -  $_{350;\,2800;\,5300;\,10300}$  range:

Colour temperature [K]: 6500

Ingress protection: IP20

Charging time [h:min]: 9.5

**Battery:** 2 x batterie li-ion. 7.4V

Battery capacity [mAh]: 5000

Material of the body: aluminium

Colour of the body: grey

**Dimensions (H/W/T/S) [mm]:** 303/72/72

## **CHARACTERISTICS**

The LED hand torch is an option for those working in the automotive workshop, mobile service, garage or construction site. The functionality of LED hand torches will benefit both professionals and DIY enthusiasts - anyone for whom good lighting is important during work or hobby activities. The torch is characterised by its long service life, powerful light output and long operation time, allowing you to focus on the task at hand. At the same time, the light emitted is comfortable for the eyes and the LED technology itself is energy-efficient.

- Luminous flux: 350, 2800, 5300, 10300lm
- Robust housing
- Dimensions: 303/72/72mm
- 4 lighting modes
- Degree of protection: IP20
- Charging time: 9,5h
- $\bullet$  Length of world with dedicated battery: 350 lm  $^{\sim}$  12 h max. 90 m range 2800 lm  $^{\sim}$  3 h max. 280 m range

5300 lm - ~ 2 h - max. 390 m range

10,300 lm -  $^{\sim}$  30 sec - max. 550 m range

## **APPLICATION**

It is used as a working luminaire for lighting workplaces, workshops, or garages.



**DETAILED CARD** 

## **TECHNICAL PARAMETERS TABLE**

Index:	608452
EAN:	5905963608452
Light source:	LED
Luminous flux of the luminaire [lm] - range:	350; 2800; 5300; 10300
Colour temperature [K]:	6500
Charging time [h:min]:	9.5
Battery:	2 x batterie li-ion. 7.4V
Battery capacity [mAh]:	5000
Diffuser colour:	transparent

Material of the body:	aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	303/72/72
Ingress protection:	IP20
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	0.910
Warranty [years]:	2
CE certificate:	<u>59/2025</u>
Manual:	Download PDF

Card creation date: 30 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

