QUEST LED EVO L 35450LM I CL. IP67 740 RW10 206W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	835407
Ingress protection:	IP67
Rated power of the luminaire [W]*:	206
Luminous flux [lm]*:	35450
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	B
Material of the body:	aluminium

CHARACTERISTICS

Quest LED EVO L, their high-bay versions: surface-mounted Quest LED EVO L HB NT and suspended Quest LED EVO L HB Z are extremely efficient floodlights and premium HB class luminaires, manufactured in Poland. Their body is made of die-cast aluminium, powder coated, without an external heat sink and ribs that make it difficult to keep clean. The diffuser is made of tempered glass, under which there are LEDs with the highest efficiency. Different types of optics, especially asymmetrical ones, provide great freedom in choosing the right solution for a specific application. Thanks to the highest tightness rating on the market (IP67) and maximum impact resistance (IK10), the floodlights will perform well in all conditions, regardless of the weather and installation location. The new version of the renowned and proven QUEST model offers even better lighting parameters, achieving an efficiency of over 170 lm/W. Quest LED EVO L meets the requirements of PN-EN 60598-2 part 5, which allows it to be classified as an illumination projector, enabling complete freedom of installation in any position, with 360° rotation and resistance to strong winds. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods. Thanks to an intuitive system of coloured latches, connector installation is simple, quick and tool-free. The HB NT version is designed for surface mounting as a highbay using dedicated brackets. The HB Z version is designed for suspension. The accessory kit includes brackets for pole mounting, a frame for flush mounting (e.g. shelters), light pollution reduction screens and protective grids in two colours with different degrees of light reduction (white RAL7016: 4%, body colour RAL7016: 8%). The models can be equipped with an external motion and twilight sensor. They are also available in the ENDURA version, resistant to elevated ambient temperatures up to 50°C. The range also includes dual-module versions with increased flux and power. DALI versions are available (in the case of a gap in a specific power rating in the range with a DALI power supply, check the ENDURA DALI versions).

APPLICATION

Quest LED EVO L is widely used in lighting educational, administrative and institutional facilities, halls, garages, passageways, warehouses, shops, as well as in the food industry and commercial and service facilities related to food products. They are an ideal solution for small sports fields, open spaces and car parks. They can be mounted as floodlights on poles and masts, on building facades, as well as surface-mounted highbays (HB NT version) and suspended highbays (HB Z version). Thanks to the flush-mounted option, they are perfect for shelters. Quest LED EVO L is an excellent choice for production plants and halls as well as large-area warehouses.

QUEST LED EVO L 35450LM I CL. IP67 740 RW10 206W

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	835407	**Working temperature [°C]:**	from -20 to +35
EAN:	5905963835407	**The number of implement units:**	2
Light source:	LED	**Number on the palette [pcs]:**	24
Rated power of the luminaire [W]:	206	**Category type:**	floodlights
Supply voltage [V]:	220 - 240	**Version:**	floodlight
Surge protection [kV]:	6	**AC voltage range [V]:**	198-264
Frequency [Hz]:	50-60	**DC voltage range [V]:**	176-280
Luminous flux [lm]:	35450	**Light distribution type:**	RW10
Luminous efficacy [lm/W]:	172	**Impact resistance:**	IK10
Energy efficiency class:	B	**Net weight [kg]:**	8.500
Electrical protection class:	I	**LED lifespan L70B50 [h]:**	158000
Colour temperature [K]:	4000	**LED lifespan L80B10 [h]:**	108000
Color rendering index (Ra) >:	70	**LED lifespan L90B10 [h]:**	108000
SDCM:	3	**Category of application:**	industrial
Diffuser material:	glass	**Warranty [years]:**	5
Diffuser type:	transparent	**CE certificate:**	76/2025
Material of the body:	aluminium	**ENEC Certificate:**	0487/ENEC/26
Colour of the body:	RAL7016	**HACCP:**	852/2004
Dimensions (H/W/T/S) [mm]:	434/550/57	**Environmental Product Declaration (EPD):**	816/2025
Mounting dimensions [mm]:	400	**Manual:**	Download PDF
Ingress protection:	IP67	**ISO Certificates:**	9001:2015, 14001:2015, 45001:2018, 50001:2018
Mounting version:	surface	**Plik LDT:**	Download

QUEST LED EVO L 35450LM I CL. IP67 740 RW10 206W

DETAILED CARD

TECHNICAL PICTURES




QUEST LED EVO L 35450LM I CL. IP67 740 RW10 206W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
840470	Quest LED Evo L recessed frame RAL7016
840449	QUEST LED EVO L protective grid RAL7016
840500	QUEST LED EVO L cover RAL7016
840081	QUEST LED EVO L protective grid RAL9003
840401	QUEST LED EVO S/M/L pole holder 1x
840418	QUEST LED EVO S/M/L pole holder 2x
840098	QUEST LED EVO XS/S/M/L wall mount MAX RAL7016 1m
840388	QUEST LED EVO S/M/L RCR set 1x




Quest LED Evo L recessed frame RAL7016 (840470)




QUEST LED EVO L protective grid RAL7016 (840449)




QUEST LED EVO L cover RAL7016 (840500)




QUEST LED EVO L protective grid RAL9003 (840081)




QUEST LED EVO S/M/L pole holder 1x (840401)



QUEST LED EVO S/M/L pole holder 2x (840418)



QUEST LED EVO XS/S/M/L wall mount MAX RAL7016 1m (840098)



QUEST LED EVO S/M/L RCR set 1x (840388)

Card creation date: 20 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 76/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl