## **QUEST LED EVO M ENDURA 25250LM DALI ZG I CL. IP67 740 120D 152W**

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index: 838866 Ingress protection: IP67 Rated power of the luminaire [W]\*: 152 25250 Luminous flux [lm]\*: 4000 Colour temperature [K]: Color rendering index (Ra) >: 70 SDCM: 3 **Electrical protection class: Energy efficiency class:** R

Material of the body: aluminium

### **CHARACTERISTICS**

The Endura version of Quest LED EVO M luminaires, their high-bay versions: surface-mounted Quest LED EVO M HB NT and suspended Quest LED EVO M HB Z are extremely efficient premium class floodlights, manufactured in Poland, adapted to operate at high temperatures (up to 50 degrees C). The body is made of die-cast aluminium, powder coated, without an external heat sink and ribs that make it difficult to keep clean. The basic version has a steel arm with a 7.5-degree scale, while the highbay endura (HB NT) version is available in surface-mounted and suspended (HB Z) versions. The diffuser is made of tempered glass, under which there are LEDs with the highest efficiency. Various types of optics, especially saymmetrical ones, provide great freedom in selecting the right solution for a specific application. Thanks to the highest tightness rating on the market (IP67) and maximum impact resistance (IK10), it will perform well in all conditions, regardless of the weather and installation location. The new version of the renowned and proven QUEST model in its smallest version offers even better lighting parameters, achieving an efficiency of over 170 lm/W. The Endura variant also meets the requirements of PN-EN 60598-2 part 5, which allows them to be classified as illumination projectors. This means complete freedom of installation in any position, with 360° rotation and resistance to strong winds – an advantage not offered by other floodlights. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods (screws). Thanks to an intuitive system of coloured latches, connector installation is simple, quick and tool-free. The accessory kit includes: pole mounting brackets (basic version); frame for flush mounting, e.g. in shelters (basic version); light pollution reduction screens (basic version); protective grilles in two colours with different degrees of light reduction (white RAL7016: 4%, body colour RAL7016: 8%). The models

### **APPLICATION**

Quest LED EVO M Endura, Quest LED EVO M Endura HB NT and Endura HB Z are used in: lighting educational, administrative and institutional facilities, halls, garages, passageways, warehouses, shops, the food industry and commercial and service facilities related to food products Illumination of buildings, small sports fields, open spaces and car parks, environments with elevated ambient temperatures (up to 50 degrees C). Installation options as a floodlight, on poles and masts, on building facades, as a surface-mounted highbay (HB NT version), suspended highbay (HB Z version), flush-mounted (e.g. shelters). The product is particularly well suited for use in factories and production halls as well as large-area warehouses, especially in areas exposed to high temperatures.



# **QUEST LED EVO M ENDURA 25250LM DALI ZG I CL. IP67 740 120D 152W**

**DETAILED CARD** 

## **TECHNICAL PARAMETERS TABLE**

| 3                                 |               |
|-----------------------------------|---------------|
| Index:                            | 838866        |
| EAN:                              | 5905963838866 |
| Light source:                     | LED           |
| Rated power of the luminaire [W]: | 152           |
| Supply voltage [V]:               | 220 - 240     |
| Surge protection [kV]:            | 6             |
| Frequency [Hz]:                   | 0/50/60       |
| Luminous flux [Im]:               | 25250         |
| Luminous efficacy [lm/W]:         | 166           |
| Energy efficiency class:          | В             |
| Electrical protection class:      | 1             |
| Colour temperature [K]:           | 4000          |
| Color rendering index (Ra) >:     | 70            |
| SDCM:                             | 3             |
| Beam angle [°]:                   | 120           |
| Diffuser material:                | glass         |
| Diffuser type:                    | transparent   |
| Material of the body:             | aluminium     |
| Colour of the body:               | RAL7016       |
| Dimensions (H/W/T/S) [mm]:        | 383/550/57    |
| Mounting dimensions [mm]:         | 400           |
| Ingress protection:               | IP67          |

| Mounting version:                        | surface         |  |
|--|-----------------|--|
| Working temperature [°C]:                | from -20 to +50 |  |
| Sockets:                                 | 1               |  |
| DIMM DALI:                               | yes             |  |
| The number of implement units:           | 1               |  |
| Number on the palette [pcs]:             | 48              |  |
| Category type:                           | floodlights     |  |
| AC voltage range [V]:                    | 90-305          |  |
| DC voltage range [V]:                    | 127-300         |  |
| Socket type:                             | ZHAGA           |  |
| Light distribution type:                 | general         |  |
| Impact resistance:                       | IK10            |  |
| Net weight [kg]:                         | 8               |  |
| LED lifespan L70B50 [h]:                 | 162000          |  |
| LED lifespan L80B20 [h]:                 | 101000          |  |
| LED lifespan L90B10 [h]:                 | 47000           |  |
| Warranty [years]:                        | 5               |  |
| CE certificate:                          | <u>77/2025</u>  |  |
| Environmental Product Declaration (EPD): | <u>816/2025</u> |  |
| Manual:                                  | Download PDF    |  |
| Category of application:                 | industrial      |  |
| Plik LDT:                                | Download        |  |
|  |                 |  |




# **QUEST LED EVO M ENDURA 25250LM DALI ZG I CL. IP67 740 120D 152W**


**DETAILED CARD** 

## **ACCESSORIES AVAILABLE**


| index  | Name                                    |
|--------|---|
| 840463 | Quest LED Evo M recessed frame RAL7016  |
| 840432 | QUEST LED EVO M protective grid RAL7016 |
| 840494 | QUEST LED EVO M cover RAL7016           |
| 840074 | QUEST LED EVO M protective grid RAL9003 |
| 840401 | QUEST LED EVO M/L pole holder 1x        |
| 840418 | QUEST LED EVO M/L pole holder 2x        |
| 840098 | QUEST LED EVO wall mount RAL7016 1m     |
| 840388 | QUEST LED EVO M/L RCR set 1x            |




Quest LED Evo M recessed frame RAL7016 (840463)




QUEST LED EVO M protective grid RAL7016 (840432)




QUEST LED EVO M cover RAL7016 (840494)




QUEST LED EVO M protective grid RAL9003 (840074)




QUEST LED EVO M/L pole holder 1x (840401)



QUEST LED EVO M/L pole holder 2x (840418)



QUEST LED EVO wall mount RAL7016 1m (840098)



QUEST LED EVO M/L RCR set 1x (840388)

Card creation date: 05 August 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

