# CONTRA LED 400MM MULTI 2900-4200LM 840 IP40 II CL. MAT PS 21-32W WHITE

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 375088 |
| **Ingress protection:** | IP40 |
| **Impact resistance:** | IK07 |
| **Rated power [W] - range:** | 21-32 |
| **Luminous flux of the luminaire [lm] - range:** | 2900-4200 |
| **Color rendering index (Ra) >:** | 80 |
| **Energy efficiency class:** | D |
| **Material of the body:** | coated aluminium |
| **Diffuser material:** | PS |
| **Diffuser type:** | matt |

## CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

## APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

# CONTRA LED 400MM MULTI 2900-4200LM 840 IP40 II CL. MAT PS 21-32W WHITE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 375088 |
| **EAN:** | 5905963375088 |
| **Light source:** | LED |
| **Rated power [W] - range:** | 21-32 |
| **Supply voltage [V]:** | 220-240 |
| **Frequency [Hz]:** | 50-60 |
| **Luminous flux of the luminaire [lm] - range:** | 2900-4200 |
| **Luminous efficacy [lm/W]:** | 132 |
| **Energy efficiency class:** | D |
| **Electrical protection class:** | II |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **Beam angle [°]:** | 114 |
| **Surge protection [kV]:** | 2 |
| **Diffuser material:** | PS |
| **Diffuser type:** | matt |
| **Diffuser colour:** | milky |
| **Optics material:** | PMMA |


| | |
|---|---|
| **Material of the body:** | coated aluminium |
| **Colour of the body:** | white |
| **Dimensions (H/W/T/S) [mm]:** | 400/400/39 |
| **Impact resistance:** | IK07 |
| **Ingress protection:** | IP40 |
| **Mounting version:** | surface |
| **Working temperature [°C]:** | from 0 to +35 |
| **Number on the palette [pcs]:** | 44 |
| **Net weight [kg]:** | 0.900 |
| **LED lifespan L70B50 [h]:** | 50000 |
| **LED lifespan L80B10 [h]:** | 100000 |
| **Light distribution type:** | lambertian |
| **Warranty [years]:** | 5 |
| **CE certificate:** | 68/2026 |
| **Environmental Product Declaration (EPD):** | 869/2025 |
| **Manual:** | Download PDF |
| **ISO Certificates:** | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| **Plik LDT:** | Download |

# CONTRA LED 400MM MULTI 2900-4200LM 840 IP40 II CL. MAT PS 21-32W WHITE

DETAILED CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| 413995 | CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish |



CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish (413995)



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 68/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl