

# CONTRA LED 400MM MULTI 2900-4200LM 840 IP40 II CL. MAT PS 21-32W WHITE

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	375088
<b>Ingress protection:</b>	IP40
<b>Impact resistance:</b>	IK07
<b>Rated power [W] - range:</b>	21-32
<b>Luminous flux of the luminaire [lm] - range:</b>	2900-4200
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	coated aluminium
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	matt

## CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

## APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

# CONTRA LED 400MM MULTI 2900-4200LM 840 IP40 II CL. MAT PS 21-32W WHITE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	375088	<b>Material of the body:</b>	coated aluminium
<b>EAN:</b>	5905963375088	<b>Colour of the body:</b>	white
<b>Light source:</b>	LED	<b>Dimensions (H/W/T/S) [mm]:</b>	400/400/39
<b>Rated power [W] - range:</b>	21-32	<b>Impact resistance:</b>	IK07
<b>Supply voltage [V]:</b>	220-240	<b>Ingress protection:</b>	IP40
<b>Frequency [Hz]:</b>	50-60	<b>Mounting version:</b>	surface
<b>Luminous flux of the luminaire [lm] - range:</b>	2900-4200	<b>Working temperature [°C]:</b>	from 0 to +35
<b>Luminous efficacy [lm/W]:</b>	132	<b>Number on the palette [pcs]:</b>	44
<b>Energy efficiency class:</b>	D	<b>Net weight [kg]:</b>	0.900
<b>Electrical protection class:</b>	II	<b>LED lifespan L70B50 [h]:</b>	50000
<b>Colour temperature [K]:</b>	4000	<b>LED lifespan L80B10 [h]:</b>	100000
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Light distribution type:</b>	lambertian
<b>Beam angle [°]:</b>	114	<b>Warranty [years]:</b>	5
<b>Surge protection [kV]:</b>	2	<b>CE certificate:</b>	<a href="#">68/2026</a>
<b>Diffuser material:</b>	PS	<b>Environmental Product Declaration (EPD):</b>	<a href="#">869/2025</a>
<b>Diffuser type:</b>	matt	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Diffuser colour:</b>	milky	<b>ISO Certificates:</b>	9001:2015, 14001:2015, 45001:2018, 50001:2018
<b>Optics material:</b>	PMMA	<b>Plik LDT:</b>	<a href="#">Download</a>

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 68/2026