

CONTRA LED 400MM MULTI 2900-4200LM 840 IP20 II CL. MAT PS 21-32W WHITE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	375088
Ingress protection:	IP20
Impact resistance:	IK07
Rated power [W] - range:	21-32
Luminous flux of the luminaire [lm] - range:	2900-4200
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	MAT

CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400MM MULTI 2900-4200LM 840 IP20 II CL. MAT PS 21-32W WHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	375088	Diffuser type:	MAT
EAN:	5905963375088	Diffuser colour:	milky
Light source:	LED	Optics material:	PMMA
Rated power [W] - range:	21-32	Optics:	lens
Colour temperature [K]:	4000	Material of the body:	coated aluminium
Luminous flux of the luminaire [lm] - range:	2900-4200	Impact resistance:	IK07
Colour of the body:	white	Ingress protection:	IP20
Supply voltage [V]:	220-240	Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	400/400/39	Working temperature [°C]:	from 0 to +35
Frequency [Hz]:	50-60	Number on the palette [pcs]:	44
Luminous efficacy [lm/W]:	132	Net weight [kg]:	0.900
Energy efficiency class:	D	LED lifespan L70B50 [h]:	50000
Electrical protection class:	II	LED lifespan L80B20 [h]:	36000
Colour rendering index:	>80	Light distribution type:	lamertian
Beam angle [°]:	114	Warranty [years]:	5
Surge protection [kV]:	2	CE certificate:	83/2025
Diffuser material:	PS	Manual:	Download PDF

Card creation date: 04 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 83/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl