CONTRA LED 400MM MULTI 2750-4000LM 840 IP40 II CL. MAT PS 21-32W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	375095
Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	21-32
Luminous flux of the luminaire [lm] - range:	2750-4000
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt

CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400MM MULTI 2750-4000LM 840 IP40 II CL. MAT PS 21-32W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	375095
EAN:	5905963375095
Light source:	LED
Rated power [W] - range:	21-32
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux of the luminaire [lm] - range:	2750-4000
Luminous efficacy [lm/W]:	125
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Beam angle [°]:	114
Surge protection [kV]:	2
Diffuser material:	PS
Diffuser type:	matt
Diffuser colour:	milky
Optics material:	PMMA


Material of the body:	coated aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	400/400/39
Impact resistance:	IK07
Ingress protection:	IP40
Mounting version:	surface
Working temperature [°C]:	from 0 to +35
Number on the palette [pcs]:	44
Net weight [kg]:	0.900
LED lifespan L70B50 [h]:	50000
LED lifespan L80B10 [h]:	100000
Light distribution type:	lambertian
Warranty [years]:	5
CE certificate:	68/2026
Environmental Product Declaration (EPD):	869/2025
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

CONTRA LED 400MM MULTI 2750-4000LM 840 IP40 II CL. MAT PS 21-32W BLACK

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
413995	CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish



CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish (413995)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 68/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl