

CONTRA LED 400MM MULTI 2750-4000LM 840 IP40 II CL. MAT PS 21-32W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	375095
Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	21-32
Luminous flux of the luminaire [lm] - range:	2750-4000
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt

CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400MM MULTI 2750-4000LM 840 IP40 II CL. MAT PS 21-32W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	375095	Material of the body:	coated aluminium
EAN:	5905963375095	Colour of the body:	black
Light source:	LED	Dimensions (H/W/T/S) [mm]:	400/400/39
Rated power [W] - range:	21-32	Impact resistance:	IK07
Supply voltage [V]:	220-240	Ingress protection:	IP40
Frequency [Hz]:	50-60	Mounting version:	surface
Luminous flux of the luminaire [lm] - range:	2750-4000	Working temperature [°C]:	from 0 to +35
Luminous efficacy [lm/W]:	125	Number on the palette [pcs]:	44
Energy efficiency class:	D	Net weight [kg]:	0.900
Electrical protection class:	II	LED lifespan L70B50 [h]:	50000
Colour temperature [K]:	4000	LED lifespan L80B10 [h]:	100000
Color rendering index (Ra) >:	80	Light distribution type:	lambertian
Beam angle [°]:	114	Warranty [years]:	5
Surge protection [kV]:	2	CE certificate:	68/2026
Diffuser material:	PS	Environmental Product Declaration (EPD):	869/2025
Diffuser type:	matt	Manual:	Download PDF
Diffuser colour:	milky	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Optics material:	PMMA	Plik LDT:	Download

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 68/2026