

CONTRA LED 400MM MULTI 2750-4000LM 840 IP40 II CL. MAT PS 21-32W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	375095
Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	21-32
Luminous flux of the luminaire [lm] - range:	2750-4000
Colour rendering index:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt

CHARACTERISTICS

Contra LED 400 MULTI is a versatile LED panel with a low, slim profile. Designed from scratch, it introduces new solutions that ensure excellent lighting parameters. The body is made of aluminium, which makes it lightweight and highly impact-resistant (IK07). The opal diffuser made of PS provides the lamp with excellent lighting properties. The integrated LED module ensures low power consumption and all the advantages of modern LED lamps. The multifunctional LED power supply provides 4 brightness levels via a built-in switch.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400MM MULTI 2750-4000LM 840 IP40 II CL. MAT PS 21-32W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	375095	Optics material:	PMMA
EAN:	5905963375095	Optics:	lens
Light source:	LED	Material of the body:	coated aluminium
Rated power [W] - range:	21-32	Colour of the body:	black
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	400/400/39
Frequency [Hz]:	50-60	Impact resistance:	IK07
Luminous flux of the luminaire [lm] - range:	2750-4000	Ingress protection:	IP40
Luminous efficacy [lm/W]:	125	Mounting version:	surface
Energy efficiency class:	D	Working temperature [°C]:	from 0 to +35
Electrical protection class:	II	Number on the palette [pcs]:	44
Colour temperature [K]:	4000	Net weight [kg]:	0.900
Colour rendering index:	80	LED lifespan L80B20 [h]:	100000
Beam angle [°]:	114	Light distribution type:	lambertian
Surge protection [kV]:	2	Warranty [years]:	5
Diffuser material:	PS	CE certificate:	85/2025
Diffuser type:	matt	Manual:	Download PDF
Diffuser colour:	milky		

Card creation date: 07 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 85/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl