

QUEST LED EVO 2XM ENDURA HB NT 59100LM DALI I CL. IP67 740 120D 370W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	829635
Ingress protection:	IP67
Rated power of the luminaire [W]*:	370
Luminous flux [lm]*:	59100
Colour temperature [K]:	4000
Colour rendering index:	70
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	B
Material of the body:	aluminium

CHARACTERISTICS

The Endura version of Quest LED EVO M luminaires, their high-bay versions: surface-mounted Quest LED EVO M HB NT and suspended Quest LED EVO M HB Z are extremely efficient premium class floodlights, manufactured in Poland, adapted to operate at high temperatures (up to 50 degrees C). The body is made of die-cast aluminium, powder coated, without an external heat sink and ribs that make it difficult to keep clean. The basic version has a steel arm with a 7.5-degree scale, while the highbay endura (HB NT) version is available in surface-mounted and suspended (HB Z) versions. The diffuser is made of tempered glass, under which there are LEDs with the highest efficiency. Various types of optics, especially asymmetrical ones, provide great freedom in selecting the right solution for a specific application. Thanks to the highest tightness rating on the market (IP67) and maximum impact resistance (IK10), it will perform well in all conditions, regardless of the weather and installation location. The new version of the renowned and proven QUEST model in its smallest version offers even better lighting parameters, achieving an efficiency of over 170 lm/W. The Endura variant also meets the requirements of PN-EN 60598-2 part 5, which allows them to be classified as illumination projectors. This means complete freedom of installation in any position, with 360° rotation and resistance to strong winds – an advantage not offered by other floodlights. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods (screws). Thanks to an intuitive system of coloured latches, connector installation is simple, quick and tool-free. The accessory kit includes: pole mounting brackets (basic version); frame for flush mounting, e.g. in shelters (basic version); light pollution reduction screens (basic version); protective grilles in two colours with different degrees of light reduction (white RAL7016: 4%, body colour RAL7016: 8%). The models can be equipped with an external motion and twilight sensor.

APPLICATION

Quest LED EVO M Endura, Quest LED EVO M Endura HB NT and Endura HB Z are used in: lighting educational, administrative and institutional facilities, halls, garages, passageways, warehouses, shops, the food industry and commercial and service facilities related to food products illumination of buildings, small sports fields, open spaces and car parks, environments with elevated ambient temperatures (up to 50 degrees C). Installation options: as a floodlight, on poles and masts, on building facades, as a surface-mounted highbay (HB NT version), suspended highbay (HB Z version), flush-mounted (e.g. shelters). The product is particularly well suited for use in factories and production halls as well as large-area warehouses, especially in areas exposed to high temperatures.

QUEST LED EVO 2XM ENDURA HB NT 59100LM DALI I CL. IP67 740 120D 370W

DETAILED CARD

TECHNICAL PARAMETERS TABLE


Index:	829635	Dimensions (H/W/T/S) [mm]:	753/635/152
EAN:	5905963829635	Ingress protection:	IP67
Rated power of the luminaire [W]:	370	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	59100	DIMM DALI:	yes
Supply voltage [V]:	220 - 240	The number of implement units:	4
AC voltage range [V]:	198-264	Dimensions of single box [mm]:	645
DC voltage range [V]:	176-280	Version:	2xM HB NT
Frequency [Hz]:	50-60	Light distribution type:	general
Luminous efficacy [lm/W]:	160	Impact resistance:	IK10
Energy efficiency class:	B	LED lifespan L70B50 [h]:	162000
Electrical protection class:	I	LED lifespan L80B20 [h]:	101000
Colour temperature [K]:	4000	LED lifespan L90B10 [h]:	47000
Colour rendering index:	70	Warranty [years]:	5
SDCM:	3	CE certificate:	81/2025
Beam angle [°]:	120	Environmental Product Declaration (EPD):	816/2025
Diffuser material:	glass	Manual:	Download PDF
Material of the body:	aluminium	Plik LDT:	Download
Colour of the body:	RAL7016		

QUEST LED EVO 2XM ENDURA HB NT 59100LM DALI I CL. IP67 740 120D 370W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
840432	QUEST LED EVO M protective grid RAL7016
840074	QUEST LED EVO M protective grid RAL9003
840388	QUEST LED EVO M/L RCR set 1x
840371	QUEST LED EVO M/L RCR set 2x




QUEST LED EVO M protective grid
RAL7016 (840432)



QUEST LED EVO M protective grid
RAL9003 (840074)



QUEST LED EVO M/L RCR set
1x (840388)



QUEST LED EVO M/L RCR set
2x (840371)

Card creation date: 06 August 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 81/2025