

QUEST LED EVO L ENDURA HB NT 34850LM I CL. IP67 740 120D 206W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	829123
Ingress protection:	IP67
Rated power of the luminaire [W]*:	206
Luminous flux [lm]*:	34850
Colour temperature [K]:	4000
Colour rendering index:	>70
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	B
Material of the body:	aluminium

CHARACTERISTICS

APPLICATION

QUEST LED EVO L ENDURA HB NT 34850LM I CL. IP67 740 120D 206W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	829123	Diffuser type:	transparent
EAN:	5905963829123	Material of the body:	aluminium
Rated power of the luminaire [W]:	206	Colour of the body:	RAL7016
Luminous flux [lm]:	34850	Dimensions (H/W/T/S) [mm]:	475/635/152
Supply voltage [V]:	220 - 240	Mounting dimensions [mm]:	590/45
AC voltage range [V]:	198-264	Ingress protection:	IP67
DC voltage range [V]:	176-280	Mounting version:	surface
Frequency [Hz]:	0/50/60	Working temperature [°C]:	from -20 to +50
Luminous efficacy [lm/W]:	169	Dimensions of single box [mm]:	640
Energy efficiency class:	B	Number on the palette [pcs]:	24
Electrical protection class:	I	Version:	L ENDURA HB NT
Colour temperature [K]:	4000	Light distribution type:	general
Colour rendering index:	>70	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	82/2025
Beam angle [°]:	120	Environmental Product Declaration (EPD):	816/2025
Diffuser material:	glass	Manual:	Download PDF

QUEST LED EVO L ENDURA HB NT 34850LM I CL. IP67 740 120D 206W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
840449	QUEST LED EVO L protective grid RAL7016
840081	QUEST LED EVO L protective grid RAL9003
840388	QUEST LED EVO M/L RCR set 1x
840371	QUEST LED EVO M/L RCR set 2x

Card creation date: 06 August 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 82/2025