TUBA IP69K PMMA 630MM 2600LM 840 AW3H MW IK05 16W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	778285
Ingress protection:	IP69K
Impact resistance:	IK05
Rated power of the luminaire [W]*:	16
Luminous flux [lm]*:	2600
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	В

CHARACTERISTICS

Tuba IP69K is a cylindrical luminaire for special tasks - where other solutions fail. Designed for extreme conditions, it combines superior sealing, chemical resistance and mechanical durability. Meeting the standard for IP69K means full protection against dust (IP6X) and complete resistance to water at extremely high pressure (100 bar) at 80°C (IPX9K). This makes the luminaire ideal for areas requiring intensive cleaning, including with powerful water jets and detergents. The IP69K tube is designed to operate in the most demanding conditions. Made from chemically resistant materials: PMMA and extremely resistant borosilicate glass - ensuring exceptional durability even in aggressive industrial environments. The turned acid-resistant steel endcap eliminates the risk of corrosion, and its resistance to ammonia and zoonotic gases makes it ideal for livestock and processing facilities. Thanks to the decompression valve, the luminaire easily withstands rapid temperature changes, and the highest Ik10 impact resistance rating (for the PC version) guarantees reliability in the harshest operating conditions.

APPLICATION

Ideal for areas requiring regular high-pressure cleaning, such as car washes, sewage treatment plants, food processing plants or slaughterhouses. It excels in environments with high humidity, sub-zero temperatures and aggressive fumes from cold stores and freezers to mushroom, animal and plant farms. Thanks to its superior chemical and mechanical resistance, it is a reliable solution for workshops and service channels. It is also ideal for industrial halls, traffic routes and even as minimalist, decorative general lighting in commercial buildings.



TUBA IP69K PMMA 630MM 2600LM 840 AW3H MW IK05 16W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	778285
EAN:	5905963778285
Light source:	LED module
Rated power of the luminaire [W]:	16
Luminous flux [lm]:	2600
Luminous efficacy [lm/W]:	163
Energy efficiency class:	В
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	137500
LED lifespan L80B20 [h]:	86500
LED lifespan L90B10 [h]:	42000
Beam angle [°]:	90
Surge protection [kV]:	1
Diffuser material:	PMMA
Diffuser colour:	transparent
Optics:	matrix lens
Optics material:	PC

Material of the body:	stainless steel
Dimensions (H/W/T/S) [mm]:	600/64.5
Mounting dimensions [mm]:	603.5
Impact resistance:	IK05
Ingress protection:	IP69K
Mounting version:	surface, suspended
Working temperature [°C]:	35
Tilt angle adjustment [°]:	yes
Wire type:	H07RN-F 3x1,5
Operating mode:	1
Emergency lighting [h]:	3
Autotest:	yes
Accessories included:	surface-mounted bracket
Number on the palette [pcs]:	154
Net weight [kg]:	2.150
Light distribution type:	MW
Warranty [years]:	5
CE certificate:	84/2025
Manual:	Download PDF



TUBA IP69K PMMA 630MM 2600LM 840 AW3H MW IK05 16W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
778254	Tuba IP69K 3P connector set
778261	Connector set Tuba IP69K 5P DALI





Tuba IP69K 3P connector set (778254)

Connector set Tuba IP69K 5P DALI (778261)

