## CONSTELIA LED 6400LM 740 RM7 IP66 II CL. DALI ZG-DOWN IK09 (52W)

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index:	809316

Ingress protection: IP66

Impact resistance: IK09

Rated power of the luminaire [W]\*: 52

Luminous flux [lm]\*: 6400

Colour temperature [K]: 4000

Color rendering index (Ra) >: 70

Optics: RM7

**Control:** Yes + 5-stage power

reduction

#### **CHARACTERISTICS**

Constelia LED is a new generation of stylised LED park-and-ride luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having dedicated optics, ensuring the light characteristics remain consistent over time. The luminaire's design ensures that the luminaire's internal chamber remains sealed. As standard, the luminaire offers tool-free access to the electrical equipment, which, if desired and to protect against vandalism or uncontrolled opening, can optionally be permanently secured with screws. The luminaire offers rapid and convenient serviceability, allowing one integrated component to be replaced without the need to dismantle the entire luminaire and make soldered or screwed connections. No on-site service work is required. Simply replace the module with a spare (accessory) close the luminaire and the service work is then carried out on site: at the luminaire owner's facility or sent back to the manufacturer's service centre. The luminaire body and handle are made of die-cast aluminium, powder-coated black and have a very high IP66 ingress protection and IK09 mechanical shock resistance.

Accessories available: NTC overheating protection; fully programmable DALI driver; luminaire CLO and Autonomous 5-step power reduction functions available; connection terminals;

tool-free access protected by a knife disconnect switch to de-energise the integral module if the compartment is opened.

Additional options: stylised glazing to transform the external appearance of the luminaire, ZHAGA connector (ZhagaBook 18); interfacing with control systems, antivandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; design with cable terminated with quick connector; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga-D4i.

#### APPLICATION

Outdoor areas of places such as town halls, libraries, town halls, health facilities, schools, kindergartens, public gardens, streets, pavements, recreational areas: playing fields, playgrounds, cycle paths, historical sites, old towns.



# CONSTELIA LED 6400LM 740 RM7 IP66 II CL. DALI ZG-DOWN IK09 (52W)


**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Index:	809316
EAN:	5905963809316
Category type:	Park and city lighting
Category of application:	parkings and bicycle paths
Light source:	LED module
Rated power of the luminaire [W]:	52
Luminous flux [Im]:	6400
Supply voltage [V]:	220-240
Luminous efficacy [lm/W]:	123
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
Power factor:	0.96
Surge protection [kV]:	10
Diffuser material:	tempered glass
Diffuser type:	transparent
Optics:	RM7
Optics material:	PMMA + PC
Material of the body:	powder coated aluminium

Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	425/425/827
Mounting dimensions [mm]:	ø76
Impact resistance:	IK09
Ingress protection:	IP66
Mounting version:	top
Working temperature [°C]:	from -40 to +50
Socket type:	ZG-DN
Sockets:	1
DIMM DALI:	yes
Control:	Yes + 5-stage power reduction
Wire type:	HO7 RNF-2x1
Cable length [m]:	1.50
Number on the palette [pcs]:	8
Net weight [kg]:	7
Warranty [years]:	5 z możliwością przedłużenia do 10
CE certificate:	<u>87/2025</u>
ENEC Certificate:	0431/ENEC/25; 0151/ENEC+/25
Zhaga-D4i:	ZG448511062025
Manual:	Download PDF

### **LIGHT CURVES**



Card creation date: 09 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

