

# CONSTELIA LED 6400LM 740 RM7 IP66 II CL. DALI ZG-DOWN IK09 (52W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	809316
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	52
Luminous flux [lm]*:	6400
Colour temperature [K]:	4000
Colour rendering index:	70
Optics:	RM7
Control:	Yes + 5-stage power reduction

## CHARACTERISTICS

Constelia LED is a new generation of stylised LED park-and-ride luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having dedicated optics, ensuring the light characteristics remain consistent over time. The luminaire's design ensures that the luminaire's internal chamber remains sealed. As standard, the luminaire offers tool-free access to the electrical equipment, which, if desired and to protect against vandalism or uncontrolled opening, can optionally be permanently secured with screws. The luminaire offers rapid and convenient serviceability, allowing one integrated component to be replaced without the need to dismantle the entire luminaire and make soldered or screwed connections. No on-site service work is required. Simply replace the module with a spare (accessory) close the luminaire and the service work is then carried out on site: at the luminaire owner's facility or sent back to the manufacturer's service centre. The luminaire body and handle are made of die-cast aluminium, powder-coated black and have a very high IP66 ingress protection and IK09 mechanical shock resistance.

Accessories available: NTC overheating protection; fully programmable DALI driver; luminaire CLO and Autonomous 5-step power reduction functions available; connection terminals;

tool-free access protected by a knife disconnect switch to de-energise the integral module if the compartment is opened.

Additional options: stylised glazing to transform the external appearance of the luminaire, ZHAGA connector (ZhagaBook 18); interfacing with control systems, anti-vandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; design with cable terminated with quick connector; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga-D4i.

## APPLICATION

Outdoor areas of places such as town halls, libraries, town halls, health facilities, schools, kindergartens, public gardens, streets, pavements, recreational areas: playing fields, playgrounds, cycle paths, historical sites, old towns.

# CONSTELIA LED 6400LM 740 RM7 IP66 II CL. DALI ZG-DOWN IK09 (52W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	809316	Colour of the body:	black
EAN:	5905963809316	Dimensions (H/W/T/S) [mm]:	425/425/827
Category type:	Park and city lighting	Mounting dimensions [mm]:	ø76
Category of application:	parkings and bicycle paths	Impact resistance:	IK09
Light source:	LED module	Ingress protection:	IP66
Rated power of the luminaire [W]:	52	Mounting version:	top
Luminous flux [lm]:	6400	Working temperature [°C]:	from -40 to +50
Supply voltage [V]:	220-240	Socket type:	ZG-DN
Luminous efficacy [lm/W]:	123	Sockets:	1
Energy efficiency class:	D	DIMM DALI:	yes
Electrical protection class:	II	Control:	Yes + 5-stage power reduction
Colour temperature [K]:	4000	Wire type:	HO7 RNF-2x1
Colour rendering index:	70	Cable length [m]:	1.50
Power factor:	0.96	Number on the palette [pcs]:	8
Surge protection [kV]:	10	Net weight [kg]:	7
Diffuser material:	tempered glass	Warranty [years]:	5 z możliwością przedłużenia do 10
Diffuser type:	transparent	CE certificate:	<a href="#">87/2025</a>
Optics:	RM7	ENEC Certificate:	<a href="#">0431/ENEC/25; 0151/ENEC+/25</a>
Optics material:	PMMA + PC	Zhaga-D4i:	<a href="#">ZG448511062025</a>
Material of the body:	powder coated aluminium	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES

