CONSTELIA LED R 3075LM 730 RM7 IP66 II CL. 2DIM SP10KV IK09 (24W)

DETAILED CARD





TECHNICAL PARAMETERS

Index: 809248

Ingress protection: IP66

Impact resistance: IK09

Rated power of the luminaire [W]*: 24

Luminous flux [lm]*: 3075

Colour temperature [K]: 3000

Color rendering index (Ra) >: 70

Optics: RM7

Control: Yes + 5-stage power

reduction

CHARACTERISTICS

Constelia LED R is a new generation of stylised LED park-and-ride luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having dedicated optics, ensuring the light characteristics remain consistent over time. The luminaire's design ensures that the luminaire's internal chamber remains sealed. As standard, the luminaire offers tool-free access to the electrical equipment, which, if desired and to protect against vandalism or uncontrolled opening, can optionally be permanently secured with screws. The luminaire offers rapid and convenient serviceability, allowing one integrated component to be replaced without the need to dismantle the entire luminaire and make soldered or screwed connections. No on-site service work is required. Simply replace the module with a spare (accessory) close the luminaire and the service work is then carried out on site: at the luminaire owner's facility or sent back to the manufacturer's service centre. The luminaire body and handle are made of die-cast aluminium, powder-coated black and have a very high IP66 ingress protection and IK09 mechanical shock resistance.

Accessories available: NTC overheating protection; fully programmable DALI

Accessories available: NTC overheating protection; fully programmable DALI driver; luminaire CLO and Autonomous 5-step power reduction functions available; connection terminals;

tool-free access protected by a knife disconnect switch to de-energise the integral module if the compartment is opened.

Additional options: stylised glazing to transform the external appearance of the luminaire, ZHAGA connector (ZhagaBook 18); interfacing with control systems, antivandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; design with cable terminated with quick connector; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga-D4i.

APPLICATION

Outdoor areas of places such as town halls, libraries, town halls, health facilities, schools, kindergartens, public gardens, streets, pavements, recreational areas: playing fields, playgrounds, cycle paths, historical sites, old towns.



CONSTELIA LED R 3075LM 730 RM7 IP66 II CL. 2DIM SP10KV IK09 (24W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	809248
Category type:	Park and city lighting
Category of application:	parkings and bicycle paths
Light source:	LED module
Rated power of the luminaire [W]:	24
Luminous flux [lm]:	3075
Supply voltage [V]:	220-240
Luminous efficacy [lm/W]:	128
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	70
SDCM:	4
Power factor:	0.96
Surge protection [kV]:	10
Diffuser material:	tempered glass
Diffuser type:	transparent
Optics:	RM7
Optics material:	PMMA + PC
Material of the body:	powder coated aluminium
Colour of the body:	black

Dimensions (H/W/T/S) [mm]:	425/425/765
Mounting dimensions [mm]:	ø42
Impact resistance:	IK09
Ingress protection:	IP66
Mounting version:	suspended
Working temperature [°C]:	from -40 to +50
DIMM 1-10V:	yes
Control:	Yes + 5-stage power reduction
Wire type:	HO7 RNF-2x1
Cable length [m]:	1.50
Protection type:	NTC + ESD + SP10kV/10kA
Number on the palette [pcs]:	8
Net weight [kg]:	7
ETIM class:	EC000062
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5 z możliwością przedłużenia do 10
CE certificate:	88/2025
ENEC Certificate:	0431/ENEC/25; 0151/ENEC+/25
Zhaga-D4i:	ZG448511062025
Manual:	Download PDF

LIGHT CURVES



Card creation date: 09 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

