

QUEST LED EVO XS HB NT 8500LM DALI I CL. IP67 740 120D 50W

DETAILED CARD



Zdjęcie poglądowe nie uwzględniające zawartych w zestawie uchwytów do montażu natynkowego.
Overview photo not including the included surface-mount brackets.



TECHNICAL PARAMETERS

Index:	839054
Ingress protection:	IP67
Impact resistance:	IK10
Rated power of the luminaire [W]*:	50
Luminous flux [lm]*:	8500
Colour temperature [K]:	4000
Colour rendering index:	70
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	B

CHARACTERISTICS

Quest LED Evo XS, their high-bay versions: surface-mounted Quest LED Evo XS HB NT and suspended Quest LED Evo XS HB Z are compact yet extremely efficient premium class floodlights manufactured in Poland. Their body is made of die-cast aluminium in corrosion class C5, powder coated, without an external heat sink and ribs that make it difficult to keep clean. The diffuser is made of tempered glass, under which there are high-performance LEDs. Various types of optics, especially asymmetrical ones, provide great freedom in selecting the right solution for a specific application. Thanks to the highest tightness on the market (IP67) and maximum impact resistance (IK10), the floodlights will work in all conditions – regardless of the weather and installation location. The new version of the recognised and proven QUEST model offers even better lighting parameters, achieving an efficiency of over 170 lm/W. Quest LED Evo XS meets the requirements of PN-EN 60598-2 part 5, which allows it to be classified as an illumination projector, enabling complete freedom of installation in any position, with 360° rotation and resistance to strong winds. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods. Thanks to an intuitive system of coloured latches, connector installation is simple, quick and tool-free. The HB NT version is designed for surface mounting as a highbay using dedicated brackets. The HB Z version is designed for suspension. The accessory kit includes brackets for pole mounting, a frame for flush mounting (e.g. shelters), light pollution reduction screens and protective grids in two colours with different degrees of light reduction (white RAL7016: 4%, body colour RAL7016: 8%). The models are also available with a built-in motion and twilight sensor (RCR remote control) and in the ENDURA version, resistant to elevated ambient temperatures up to 50°C. In addition, a version designed for RGB+W illumination and for surface-mounted and suspended installation as a highbay is available.

APPLICATION

Quest LED Evo XS floodlights and their surface-mounted versions, Quest LED Evo XS HB NT, are widely used in lighting educational, administrative and recreational facilities, halls, garages, passageways, warehouses, shops, as well as in the food industry and commercial and service facilities related to food products. They are the ideal solution for illuminating buildings, small sports fields, open spaces and car parks. They can be mounted as floodlights on poles and masts, on building facades, as well as surface-mounted highbays (HB NT version) and suspended highbays (HB Z version). Thanks to the flush-mounted option, they are perfect for shelters. Quest LED Evo XS is an excellent choice for factories, production halls and large warehouses.

QUEST LED EVO XS HB NT 8500LM DALI I CL. IP67 740 120D 50W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	839054	Dimensions (H/W/T/S) [mm]:	280/240/55 (390/310/325)
EAN:	5905963839054	Mounting dimensions [mm]:	265/45
Light source:	LED	Impact resistance:	IK10
Rated power of the luminaire [W]:	50	Ingress protection:	IP67
Supply voltage [V]:	220 - 240	Mounting version:	surface
Frequency [Hz]:	50-60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	8500	DIMM DALI:	yes
Luminous efficacy [lm/W]:	170	Number on the palette [pcs]:	45
Energy efficiency class:	B	Net weight [kg]:	2.900
Electrical protection class:	I	Category type:	floodlights
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	165 000
Colour rendering index:	70	LED lifespan L80B20 [h]:	103 000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	48 000
Beam angle [°]:	120	Version:	HB surface
Surge protection [kV]:	6	Light distribution type:	symmetric
Diffuser material:	glass	Warranty [years]:	5
Diffuser type:	transparent	CE certificate:	02/2025
Material of the body:	aluminium	Environmental Product Declaration (EPD):	
Colour of the body:	RAL7016	Manual:	Download PDF

QUEST LED EVO XS HB NT 8500LM DALI I CL. IP67 740 120D 50W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WSEL438	Remote control for motion sensor HD01R
840395	QUEST LED EVO XS pole holder
840425	QUEST LED EVO XS protective grid RAL7016
840456	QUEST LED EVO XS recessed frame RAL7016
840487	QUEST LED EVO XS cover RAL7016
881732	QUEST LED EVO XS protective grid RAL9003



Remote control for motion sensor
HD01R (WSEL438)

Card creation date:16 July 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 02/2025