QUEST LED EVO XS ENDURA HB NT 5900LM I CL. IP67 740 RM20 41W

DETAILED CARD



Zdjęcie poglądowe nie uwzględniające zawartych w zestawie uchwytów do montażu natynkowego.
Overview photo not including the included surface-mount brackets.

TECHNICAL PARAMETERS

Index:	839870
Ingress protection:	IP67
Impact resistance:	IK10
Rated power of the luminaire [W]*:	41
Luminous flux [lm]*:	5900
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	C

CHARACTERISTICS

The Endura version of Quest LED Evo XS luminaires, their high-bay versions: surface-mounted Quest LED Evo XS HB NT and suspended Quest LED Evo XS HB Z are compact yet extremely efficient premium floodlights, manufactured in Poland, adapted to operate at high temperatures (up to 50 degrees C). The body is made of die-cast aluminium in corrosion class C5, powder coated, without an external heat sink and fins that make it difficult to keep clean. The basic version has a steel arm with a 7.5-degree scale, while the highbay endura (HB NT) version is available in a surface-mounted form. The diffuser is made of tempered glass, under which there are LEDs with the highest efficiency. Different types of optics, especially asymmetrical ones, provide great freedom in choosing the right solution for a specific application. Thanks to the highest tightness rating on the market (IP67) and maximum impact resistance (IK10), it will perform well in all conditions, regardless of the weather and installation location. The new version of the renowned and proven QUEST model in its smallest version offers even better lighting parameters, achieving an efficiency of over 170 lm/W. The Endura variant also meets the requirements of PN-EN 60598-2 part 5, which allows them to be classified as illumination projectors. This means complete freedom of installation in any position, with 360° rotation and resistance to strong winds – an advantage not offered by other floodlights. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods (screws). Thanks to an intuitive system of coloured latches, connector installation is simple, quick and tool-free. The accessory kit includes: pole mounting brackets (basic version); frame for flush mounting, e.g. in shelters (basic version); light pollution reduction screens (basic version); protective grids in two colours with different degrees of light reduction (white RAL7016: 4%, body colour RAL7016: 8%).

APPLICATION

Quest LED Evo XS Endura and Quest LED Evo XS Endura HB NT are used in: lighting educational, administrative and institutional facilities, halls, garages, passageways, warehouses, shops, the food industry and commercial and service facilities related to food products. Illumination of buildings, small sports fields, open spaces and car parks, environments with elevated ambient temperatures (up to 50 degrees C). Installation options: as a floodlight, on poles and masts, on building facades, as a surface-mounted highbay (HB NT version), suspended highbay (HB Z version), flush-mounted (e.g. shelters). The product is particularly well suited for use in factories and production halls as well as large-area warehouses, especially in areas exposed to high temperatures.

QUEST LED EVO XS ENDURA HB NT 5900LM I CL. IP67 740 RM20 41W

DETAILED CARD

TECHNICAL PARAMETERS TABLE


Index:	839870
EAN:	5905963839870
Light source:	LED
Rated power of the luminaire [W]:	41
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50-60
Luminous flux [lm]:	5900
Luminous efficacy [lm/W]:	144
Energy efficiency class:	C
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
SDCM:	3
Surge protection [kV]:	6
Diffuser material:	glass
Diffuser type:	transparent
Material of the body:	aluminium
Colour of the body:	RAL7016
Dimensions (H/W/T/S) [mm]:	280/240/55 (390/310/325)
Mounting dimensions [mm]:	265/45
Impact resistance:	IK10
Ingress protection:	IP67

Mounting version:	surface
Working temperature [°C]:	from -40 to +50
The number of implement units:	1
Number on the palette [pcs]:	45
Net weight [kg]:	2.900
Category type:	floodlights
AC voltage range [V]:	100-305
Version:	HB surface
Light distribution type:	RM20
LED lifespan L70B50 [h]:	165 000
LED lifespan L80B10 [h]:	108000
LED lifespan L90B10 [h]:	108000
Corrosivity category:	C5-M
Category of application:	industrial
Warranty [years]:	5
CE certificate:	02/2025
ENEC Certificate:	
HACCP:	852/2004
Environmental Product Declaration (EPD):	816/2025
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

QUEST LED EVO XS ENDURA HB NT 5900LM I CL. IP67 740 RM20 41W

DETAILED CARD

TECHNICAL PICTURES




QUEST LED EVO XS ENDURA HB NT 5900LM I CL. IP67 740 RM20 41W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
840395	QUEST LED EVO XS pole holder
840425	QUEST LED EVO XS protective grid RAL7016
840456	QUEST LED EVO XS recessed frame RAL7016
840487	QUEST LED EVO XS cover RAL7016
881732	QUEST LED EVO XS protective grid RAL9003
840098	QUEST LED EVO XS/S/M/L wall mount MAX RAL7016 1m
WSE0005	RC MOS MR004 IoT programming remote control
833595	QUEST LED EVO XS holder HBZ RAL7016




QUEST LED EVO XS pole holder (840395)




QUEST LED EVO XS protective grid RAL7016 (840425)




QUEST LED EVO XS recessed frame RAL7016 (840456)




QUEST LED EVO XS cover RAL7016 (840487)



QUEST LED EVO XS protective grid RAL9003 (881732)



QUEST LED EVO XS/S/M/L wall mount MAX RAL7016 1m (840098)



RC MOS MR004 IoT programming remote control (WSE0005)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 02/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl