

TERRACO DIR LED ALU 600LM IP54 | CL. 730 RW10 6W GRAPHITE

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|------------------|
| Index: | 774591 |
| Rated power of the luminaire [W]*: | 6 |
| Luminous flux [lm]*: | 600 |
| Energy efficiency class: | F |
| Electrical protection class: | I |
| Colour temperature [K]: | 3000 |
| Color rendering index (Ra) >: | 70 |
| Material of the body: | coated aluminium |

CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.


TERRACO DIR LED ALU 600LM IP54 I CL. 730 RW10 6W GRAPHITE

DETAILED CARD


TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|----------------------------|------------------------------|
| Index: | 774591 | Material of the body: | coated aluminium |
| EAN: | 5905963774591 | Colour of the body: | graphite |
| Rated power of the luminaire [W]: | 6 | Dimensions (H/W/T/S) [mm]: | 260/110/100 |
| Luminous flux [lm]: | 600 | Impact resistance: | IK04 |
| Frequency [Hz]: | 50-60 | Ingress protection: | IP54 |
| Luminous efficacy [lm/W]: | 100 | Mounting version: | surface |
| Energy efficiency class: | F | Working temperature [°C]: | from -20 to +35 |
| Electrical protection class: | I | Supply voltage [V]: | 220 - 240 |
| Colour temperature [K]: | 3000 | Optics material: | PMMA |
| Color rendering index (Ra) >: | 70 | Warranty [years]: | 5 |
| Light distribution type: | DIR | CE certificate: | 101/2025 |
| Optics: | RW10 | Manual: | Download PDF |
| Diffuser material: | PMMA | Category of application: | architectural |
| Diffuser colour: | transparent | Plik LDT: | Download |

TECHNICAL DETAILS



Dir



Dir

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).  Certificate CE - Nr: 101/2025