

TERRACO DIR LED ALU 600LMIP54 I CL. 730 RW10 6W GREY

DETAILED CARD



TECHNICAL PARAMETERS

Index:	774430
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	600
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	70
Material of the body:	coated aluminium

CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.


TERRACO DIR LED ALU 600LMIP54 I CL. 730 RW10 6W GREY

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	774430	Material of the body:	coated aluminium
EAN:	5905963774430	Colour of the body:	gray RAL 9006
Rated power of the luminaire [W]:	6	Dimensions (H/W/T/S) [mm]:	260/110/100
Luminous flux [lm]:	600	Impact resistance:	IK04
Frequency [Hz]:	50-60	Ingress protection:	IP54
Luminous efficacy [lm/W]:	100	Mounting version:	surface
Energy efficiency class:	F	Working temperature [°C]:	from -20 to +35
Electrical protection class:	I	Supply voltage [V]:	220 - 240
Colour temperature [K]:	3000	Optics material:	PMMA
Color rendering index (Ra) >:	70	Warranty [years]:	5
Light distribution type:	DIR	CE certificate:	101/2025
Optics:	RW10	Manual:	Download PDF
Diffuser material:	PMMA	Category of application:	architectural
Diffuser colour:	transparent	Plik LDT:	Download

TECHNICAL DETAILS



Dir



Dir