TERRACO DIR LED ALU 1400LM IP54 I CL. 730 RM8 12W WHITE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	774409
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1400
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	70
Material of the body:	coated aluminium

CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.


TERRACO DIR LED ALU 1400LM IP54 I CL. 730 RM8 12W WHITE

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	774409	**Material of the body:**	coated aluminium
EAN:	5905963774409	**Colour of the body:**	white (RAL 9016)
Rated power of the luminaire [W]:	12	**Dimensions (H/W/T/S) [mm]:**	260/110/100
Luminous flux [lm]:	1400	**Impact resistance:**	IK04
Frequency [Hz]:	50-60	**Ingress protection:**	IP54
Luminous efficacy [lm/W]:	117	**Mounting version:**	surface
Energy efficiency class:	F	**Working temperature [°C]:**	from -20 to +35
Electrical protection class:	I	**Supply voltage [V]:**	220 - 240
Colour temperature [K]:	3000	**Optics material:**	PMMA
Color rendering index (Ra) >:	70	**Warranty [years]:**	5
Light distribution type:	DIR	**CE certificate:**	91/2025
Optics:	RM8	**Manual:**	Download PDF
Diffuser material:	PMMA	**Category of application:**	architectural
Diffuser colour:	transparent	**Plik LDT:**	Download

TECHNICAL DETAILS



Dir



Dir

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 91/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl