## TERRACO DIR LED ALU 1400LM IP54 I CL. 730 RM8 12W WHITE

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index: 774409

Rated power of the luminaire [W]\*: 12

Luminous flux [lm]\*: 1400

Energy efficiency class:

Electrical protection class:

Colour temperature [K]: 3000

Color rendering index (Ra) >: 70

Material of the body: coated aluminium

#### **CHARACTERISTICS**

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

#### **APPLICATION**

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.



# TERRACO DIR LED ALU 1400LM IP54 I CL. 730 RM8 12W WHITE


**DETAILED CARD** 


#### **TECHNICAL PARAMETERS TABLE**

Index:	774409
EAN:	5905963774409
Rated power of the luminaire [W]:	12
Luminous flux [Im]:	1400
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	117
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	70
Light distribution type:	DIR
Optics:	RM8
Diffuser material:	PMMA
Diffuser colour:	transparent

Material of the body:	coated aluminium
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	260/110/100
Impact resistance:	IK04
Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220 - 240
Optics material:	PMMA
Warranty [years]:	5
CE certificate:	91/2025
Manual:	Download PDF
Category of application:	architectural
Plik LDT:	Download

#### **TECHNICAL DETAILS**





Dir Di

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

