

# SKVER S A 3425LM 830 MLS IP66 II CL. 1DIM B 0 (26W)

## DETAILED CARD



### TECHNICAL PARAMETERS

Index:	435119
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	26
Luminous flux [lm]*:	3425
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	II
Optics:	no
Control:	5-stage power reduction

### CHARACTERISTICS

Skver LED S (A) is the new generation of LED park and urban luminaires. It utilizes directional multi-lens arrays made of PMMA, each lens having the same optics, ensuring consistent light characteristics over time. The luminaire's design ensures the tightness of the internal chamber. As standard, the luminaire offers tool-free access to the electrical equipment using two independent knobs, which, upon request and for protection against vandalism or unauthorized opening, can be permanently secured with screws. The upper part of the luminaire features a dedicated hinge. The luminaire allows for the replacement of the integrated internal power/lighting module (compliant with ZhagaBook 13 and ZhagaBook 15 standards) without the use of tools, enabling quick and convenient servicing, allowing for the exchange of one integrated component without dismantling the entire luminaire and making soldered or screwed connections. There is no need for servicing at the installation site. Simply replace the module with a spare (accessory), close the luminaire, and then carry out the servicing work at the service location: at the luminaire owner's facility or return it to the manufacturer's service. The body and bracket are made of pressure die-cast aluminum, powder-coated in black, characterized by a very high degree of IP66 tightness and IK10 mechanical impact resistance. Standard equipment: protection against accidental luminaire overheating NTC; fully programmable DALI driver; available constant light output maintenance functions over time CLO and autonomous, 5-step power reduction; connection terminals; tool-free access. Additional options: accessory canopies transforming the external appearance of the luminaire, Zhaga connector (ZhagaBook 18); compatibility with control systems, anti-vandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; knife switch disconnecting the integrated module voltage in case of chamber opening; made with a wire terminated with a quick connector; painting in any color from the RAL palette. Certificates: CE, RoHS, ENEC, ENEC+, Zhaga-D4i.

### APPLICATION

External areas of places such as: town halls, libraries, city offices, healthcare facilities, schools, preschools, public gardens, streets, sidewalks, recreational areas: sports fields, playgrounds, bike paths, historical sites, old towns.


# SKVER S A 3425LM 830 MLS IP66 II CL. 1DIM B 0 (26W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	435119	Colour of the body:	black
EAN:	5905963435119	Dimensions (H/W/T/S) [mm]:	427/360/360
ETIM class:	EC000062	Mounting dimensions [mm]:	76/60/48
Category type:	Park and city lighting	Impact resistance:	IK10
Version:	A	Ingress protection:	IP66
Light source:	LED module	Mounting version:	Top, on pole
Rated power of the luminaire [W]:	26	Lateral surface (SCx) [m2]:	0.086
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -40 to +50
Frequency [Hz]:	50 - 60	LED lifespan L95B10 [h]:	100000
Luminous flux [lm]:	3425	DIMM 1-10V:	yes
Luminous efficacy [lm/W]:	132	Control:	5-stage power reduction
Energy efficiency class:	D	Protection type:	NTC + ESD
Electrical protection class:	II	Net weight [kg]:	5.560
Colour temperature [K]:	3000	Wire type:	HO7 RNF-2x1
Colour rendering index:	80	Warranty [years]:	5
SDCM:	≤ 4	ENEC Certificate:	<a href="#">0351/ENEC/24/M1;</a> <a href="#">0121/ENEC+/24/M2</a>
Diffuser material:	PC	CE certificate:	<a href="#">49/2024</a>
Diffuser type:	transparent	Zhaga-D4i:	<a href="#">ZG430121062024</a>
Optics:	no	Environmental Product Declaration (EPD):	<a href="#">683/2024</a>
Material of the body:	powder coated aluminium	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



# SKVER S A 3425LM 830 MLS IP66 II CL. 1DIM B 0 (26W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
435515	SKVER Backshield RAL9005
435522	SKVER Hood example 1 RAL9005
421518	SKVER Hood ULR example 2 RAL9005
4355461	SKVER cover fi 48mm
435478	SKVER cover fi 60mm



SKVER Backshield RAL9005 (435515)



SKVER Hood example 1  
RAL9005 (435522)



SKVER Hood ULR example 2  
RAL9005 (421518)