

DIRECTO S M 3H AT BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	781667
Ingress protection:	IP20
Nominal power [W]:	3
Electrical protection class:	II
Diffuser material:	PC
Diffuser type:	PMMA
Emergency lighting [h]:	3
Battery:	NiCd
Operating mode:	M/NM
Autotest:	yes

CHARACTERISTICS

Raccord d'urgence pour montage en saillie, disponible en version maintenue ou non maintenue. Le corps est en polycarbonate ; la plaque de montage est en PMMA. Batterie NiCd avec fonction de test manuel incluse, l'autonomie de la batterie en cas d'urgence est de 3 heures. Une large gamme d'accessoires optionnels est disponible - kit de montage encastré, support de montage pour drapeau, kit de montage suspendu.

APPLICATION

La tâche principale du luminaire de secours indépendant est d'indiquer la direction des voies d'évacuation et des sorties de secours après une coupure de courant, c'est-à-dire en mode sécurisé. Convient pour un montage au mur ou au plafond. Particulièrement recommandé pour les locaux techniques (couloirs, escaliers, garages, sous-sols) où un éclairage de secours permanent est nécessaire.

DIRECTO S M 3H AT BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	781667	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface
Nominal power [W]:	3	Working temperature [°C]:	od +10 do +40
Supply voltage [V]:	220-240	Emergency lighting [h]:	3
Frequency [Hz]:	50-60	Category type:	emergency lighting
Electrical protection class:	II	Autotest:	yes
LED lifespan L70B50 [h]:	50000	Operating mode:	M/NM
Battery:	NiCd	Warranty [years]:	2
Battery capacity [mAh]:	900	CE certificate:	14/2025
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	PMMA	Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	255/199		

DIRECTO S M 3H AT BLACK

DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
897238	DIRECTO S suspended mounting kit
897245	DIRECTO S Flag Mounting Kit
897252	DIRECTO S Recessed Mounting Kit



DIRECTO S suspended mounting kit (897238)



DIRECTO S Flag Mounting Kit (897245)



DIRECTO S Recessed Mounting Kit (897252)

Card creation date: 09 August 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 14/2025