QUEST LED EVO EVEREST 34700LM DALI I CL. IP66 850 75D 256W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	831119
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	256
Luminous flux [lm]*:	34700
Colour temperature [K]:	5000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

The Quest LED Evo Everest is the pinnacle of technology in the field of high-bay luminaires. The latest, largest and most powerful member of the renowned and proven QUEST family, designed for the most demanding production, logistics and warehouse spaces. It combines exceptional light efficiency, uncompromising durability and an aesthetic, industrial design. It is a modern, premium-class industrial luminaire, manufactured in Poland, designed for use in demanding environments thanks to its die-cast aluminium body, without an external heat sink and fins that make it difficult to keep clean, while perfectly dissipating excess heat. The diffuser is made of tempered glass, under which are high-performance LEDs. Various types of optics, especially asymmetrical ones, provide great freedom in selecting the right solution for a specific application. Thanks to the highest tightness rating on the market (IP66) and maximum impact resistance (IK10), EVEREST will perform well in all conditions – regardless of the weather and installation location, with an efficiency of 170 lm/W. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods. Thanks to an intuitive system of coloured latches, connecting the lamp is simple, quick and tool-free. A set of accessories allows you to expand the lamp with an additional module or modules, significantly increasing its lighting capabilities, which is particularly important for high halls. Models available with Zhaga D4i module.

APPLICATION

Quest LED Evo Everest is widely used in lighting educational, administrative and institutional facilities, halls, garages, passageways, warehouses, shops, as well as in the food industry and commercial and service facilities related to food products. They can be used as a solution for sports fields, open spaces and car parks.

QUEST LED EVO EVEREST 34700LM DALI I CL. IP66 850 75D 256W

DETAILED CARD

TECHNICAL PARAMETERS TABLE


Index:	831119
EAN:	590596831119
Light source:	LED
Rated power of the luminaire [W]:	256
Luminous flux [lm]:	34700
Supply voltage [V]:	220-240
Frequency [Hz]:	0/50/60
Luminous efficacy [lm/W]:	136
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	5000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	161000
LED lifespan L80B10 [h]:	108000
LED lifespan L90B10 [h]:	108000
Beam angle [°]:	75
Diffuser material:	glass
Diffuser type:	transparent
Optics material:	PC
Optics:	lens

Material of the body:	aluminium
Colour of the body:	RAL7016
Dimensions (H/W/T/S) [mm]:	570/441/87
Mounting dimensions [mm]:	542/366
Impact resistance:	IK10
Ingress protection:	IP66
Mounting version:	suspended
Working temperature [°C]:	from -20 to +35
DIMM DALI:	yes
The number of implement units:	1
Dimensions of single box [mm]:	572
Number on the palette [pcs]:	42
Net weight [kg]:	9.200
Surge protection [kV]:	6
Warranty [years]:	5
CE certificate:	98/2025
Environmental Product Declaration (EPD):	816/2025
HACCP:	852/2004
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

QUEST LED EVO EVEREST 34700LM DALI I CL. IP66 850 75D 256W

DETAILED CARD

TECHNICAL PICTURES




QUEST LED EVO EVEREST 34700LM DALI I CL. IP66 850 75D 256W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
831720	QUEST EVO EVEREST protective grid RAL9003
831713	QUEST EVO EVEREST protective grid RAL7016
831782	QUEST EVO EVEREST holder AW RAL7016
831775	QUEST EVO EVEREST holder RCR RAL7016
831768	QUEST EVO EVEREST luminaire connector - separate suspension RAL7016
831751	QUEST EVO EVEREST luminaire connector - common suspension RAL7016
831744	QUEST EVO EVEREST holder NT RAL7016
831737	QUEST EVO EVEREST recessed frame RAL7016




QUEST EVO EVEREST protective grid RAL9003 (831720)




QUEST EVO EVEREST protective grid RAL7016 (831713)




QUEST EVO EVEREST holder AW RAL7016 (831782)




QUEST EVO EVEREST holder RCR RAL7016 (831775)




QUEST EVO EVEREST luminaire connector - separate suspension RAL7016 (831768)



QUEST EVO EVEREST luminaire connector - common suspension RAL7016 (831751)



QUEST EVO EVEREST holder NT RAL7016 (831744)



QUEST EVO EVEREST recessed frame RAL7016 (831737)

Card creation date: 04 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 98/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl