QUEST LED EVO EVEREST ENDURA 33700LM DALI I CL. IP66 840 120D 203W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	832123
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	203
Luminous flux [lm]*:	33700
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	B

CHARACTERISTICS

Quest LED Evo Everest Endura is the pinnacle of technology in the field of high-bay luminaires. The latest, largest and most powerful member of the renowned and proven QUEST family, designed for the most demanding production, logistics and warehouse spaces. It combines exceptional light efficiency, uncompromising durability and an aesthetic, industrial design. It is a modern, premium-class industrial luminaire, manufactured in Poland, designed for use in demanding environments thanks to its die-cast aluminium body, without an external heat sink and fins that make it difficult to keep clean, while perfectly dissipating excess heat. The diffuser is made of tempered glass, under which are high-performance LEDs. Various types of optics, especially asymmetrical ones, provide great freedom in selecting the right solution for a specific application. Thanks to the highest tightness rating on the market (IP66) and maximum impact resistance (IK10), EVEREST will perform well in all conditions – regardless of the weather and installation location, with an efficiency of 170 lm/W. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods. Thanks to an intuitive system of coloured latches, connecting the lamp is simple, quick and tool-free. A set of accessories allows you to expand the lamp with an additional module or modules, significantly increasing its lighting capabilities, which is particularly important for high halls. Models available with Zhaga D4i module.

APPLICATION

Quest LED Evo Everest Endura is widely used in lighting educational, administrative and institutional facilities, halls, garages, passageways, warehouses, shops, as well as in the food industry and commercial and service facilities related to food products. They can be used as a solution for sports fields, open spaces and car parks.

QUEST LED EVO EVEREST ENDURA 33700LM DALI I CL. IP66 840 120D 203W

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	832123	**Colour of the body:**	RAL7016
EAN:	590596832123	**Dimensions (H/W/T/S) [mm]:**	570/441/87
Light source:	LED	**Mounting dimensions [mm]:**	542/366
Rated power of the luminaire [W]:	203	**Impact resistance:**	IK10
Luminous flux [lm]:	33700	**Ingress protection:**	IP66
Supply voltage [V]:	220-240	**Mounting version:**	suspended
Frequency [Hz]:	0/50/60	**Working temperature [°C]:**	from -40 to +50
Luminous efficacy [lm/W]:	166	**DIMM DALI:**	yes
Energy efficiency class:	B	**The number of implement units:**	1
Electrical protection class:	I	**Dimensions of single box [mm]:**	572
Colour temperature [K]:	4000	**Number on the palette [pcs]:**	42
Color rendering index (Ra) >:	80	**Net weight [kg]:**	9.200
SDCM:	3	**Surge protection [kV]:**	6
LED lifespan L70B50 [h]:	161000	**Warranty [years]:**	5
LED lifespan L80B10 [h]:	100500	**CE certificate:**	99/2025
LED lifespan L90B10 [h]:	47500	**Environmental Product Declaration (EPD):**	816/2025
Beam angle [°]:	120	**HACCP:**	852/2004
Diffuser material:	glass	**Manual:**	Download PDF
Diffuser type:	transparent	**ISO Certificates:**	9001:2015, 14001:2015, 45001:2018, 50001:2018
Material of the body:	aluminium	**Plik LDT:**	Download

QUEST LED EVO EVEREST ENDURA 33700LM DALI I CL. IP66 840 120D 203W

DETAILED CARD

TECHNICAL PICTURES




QUEST LED EVO EVEREST ENDURA 33700LM DALI I CL. IP66 840 120D 203W


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
831720	QUEST EVO EVEREST protective grid RAL9003
831713	QUEST EVO EVEREST protective grid RAL7016
831782	QUEST EVO EVEREST holder AW RAL7016
831775	QUEST EVO EVEREST holder RCR RAL7016
831768	QUEST EVO EVEREST luminaire connector - separate suspension RAL7016
831751	QUEST EVO EVEREST luminaire connector - common suspension RAL7016
831744	QUEST EVO EVEREST holder NT RAL7016
831737	QUEST EVO EVEREST recessed frame RAL7016




QUEST EVO EVEREST protective grid RAL9003 (831720)




QUEST EVO EVEREST protective grid RAL7016 (831713)




QUEST EVO EVEREST holder AW RAL7016 (831782)




QUEST EVO EVEREST holder RCR RAL7016 (831775)




QUEST EVO EVEREST luminaire connector - separate suspension RAL7016 (831768)



QUEST EVO EVEREST luminaire connector - common suspension RAL7016 (831751)



QUEST EVO EVEREST holder NT RAL7016 (831744)



QUEST EVO EVEREST recessed frame RAL7016 (831737)

Card creation date: 04 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 99/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl