

SOLANTO QUATTRO MULTI Z 2X600MM+2X900MM 6906-12190LM 830 IP20 I CL. OPAL WHITE 120-212W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	120-212
Luminous flux of the luminaire [lm] - range:	6906-12190
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Diffuser type:	OPAL
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	2x Ø 900/32.2x Ø 602/32
Mounting version:	suspended

CHARACTERISTICS

A suspended LED lamp made up of two rings of 602mm diameter and two rings of 900mm diameter, allowing for an attractive arrangement of representative interiors. The lamp is made of powder-coated steel in white, black or any other colour to match the character of the interior. The thermoformed milk shades emphasise the decorative character of the lamp. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings, increasing the versatility and functionality of the lamp while keeping the number of indexes to a minimum.

APPLICATION

Solanto Quattro is an extremely impressive pendant lamp, dedicated to interiors such as lobbies, receptions, shopping malls and showrooms. It is also perfect for flats and flats, blending in perfectly with stylish surroundings.

SOLANTO QUATTRO MULTI Z 2X600MM+2X900MM 6906-12190LM 830 IP20 I CL. OPAL WHITE 120-212W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	467493	LED lifespan L90B10 [h]:	35700
EAN:	5905963467493	Efficiency of the luminaire:	0.80
Category of application:	architectural, HoReCa	Diffuser material:	PMMA
Light source:	LED module	Diffuser type:	OPAL
Rated power [W] - range:	120-212	Diffuser colour:	milky
Luminous flux of the luminaire [lm] - range:	6906-12190	Material of the body:	Steel
Supply voltage [V]:	220-240	Colour of the body:	white
Frequency [Hz]:	50-60	Ring material:	Steel
Luminous efficacy [lm/W]:	58	Dimensions (H/W/T/S) [mm]:	2x Ø 900/32.2x Ø 602/32
Energy efficiency class:	G	Ingress protection:	IP20
Electrical protection class:	I	Mounting version:	suspended
Colour temperature [K]:	3000	Cable length [m]:	1.20
Color rendering index (Ra) >:	80	Dimensions of single box [mm]:	903/903/108 x2
SDCM:	3	Number on the palette [pcs]:	1
Power factor:	0.90	Warranty [years]:	5
LED lifespan L70B50 [h]:	116600	CE certificate:	12/2025
LED lifespan L80B10 [h]:	73600	Manual:	Download PDF

Card creation date: 12 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 12/2025