SOLANTO QUATTRO MULTI Z 2X600MM+2X900MM 6906-12190LM 830 IP20 I CL. OPAL WHITE 120-212W

DETAILED CARD





TECHNICAL PARAMETERS

Light source: LED module

Rated power [W] - range: 120-212

Luminous flux of the luminaire [lm] - 6906-12190 range:

Colour temperature [K]: 3000

Color rendering index (Ra) >: 80

Diffuser type: OPAL

Colour of the body: white

Dimensions (H/W/T/S) [mm]: 2x Ø 900/32.2x Ø 602/32

Mounting version: suspended

CHARACTERISTICS

A suspended LED lamp made up of two rings of 602mm diameter and two rings of 900mm diameter, allowing for an attractive arrangement of representative interiors. The lamp is made of powder-coated steel in white, black or any other colour to match the character of the interior. The thermoformed milk shades emphasise the decorative character of the lamp. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings, increasing the versatility and functionality of the lamp while keeping the number of indexes to a minimum.

APPLICATION

Solanto Quattro is an extremely impressive pendant lamp, dedicated to interiors such as lobbies, receptions, shopping malls and showrooms. It is also perfect for flats and flats, blending in perfectly with stylish surroundings.



SOLANTO QUATTRO MULTI Z 2X600MM+2X900MM 6906-12190LM 830 IP20 I CL. OPAL WHITE 120-212W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	467493
EAN:	5905963467493
Category of application:	architectural, HoReCa
Light source:	LED module
Rated power [W] - range:	120-212
Luminous flux of the luminaire [lm] - range:	6906-12190
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	58
Energy efficiency class:	G
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.90
LED lifespan L70B50 [h]:	116600
LED lifespan L80B20 [h]:	73600

LED lifespan L90B10 [h]:	35700
Efficiency of the luminaire:	0.80
Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	white
Ring material:	Steel
Dimensions (H/W/T/S) [mm]:	2x Ø 900/32.2x Ø 602/32
Ingress protection:	IP20
Mounting version:	suspended
Cable length [m]:	1.20
Dimensions of single box [mm]:	903/903/108 x2
Number on the palette [pcs]:	1
Warranty [years]:	5
CE certificate:	12/2025
Manual:	Download PDF

Card creation date: 12 September 2025



