QUEST LED EVO XS ENDURA HBZ 6000LM I CL. IP67 840 CN (33X68D) 41W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	798559
Ingress protection:	IP67
Impact resistance:	IK10
Rated power of the luminaire [W]*:	41
Luminous flux [lm]*:	6000
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	1
Energy efficiency class:	С

CHARACTERISTICS

The Endura version of Quest LED Evo XS luminaires, their high-bay versions: surface-mounted Quest LED Evo XS HB NT and suspended Quest LED Evo XS HB Z are compact yet extremely efficient premium floodlights, manufactured in Poland, adapted to operate at high temperatures (up to 50 degrees C). The body is made of die-cast aluminium in corrosion class C5, powder coated, without an external heat sink and fins that make it difficult to keep clean. The basic version has a steel arm with a 7.5-degree scale, while the highbay endura (HB NT) version is available in a surface-mounted form. The diffuser is made of tempered glass, under which there are LEDs with the highest efficiency. Different types of optics, especially asymmetrical ones, provide great freedom in choosing the right solution for a specific application. Thanks to the highest tightness rating on the market (IP67) and maximum impact resistance (IK10), it will perform well in all conditions, regardless of the weather and installation location. The new version of the renowned and proven QUEST model in its smallest version offers even better lighting parameters, achieving an efficiency of over 170 Im/W. The Endura variant also meets the requirements of PN-EN 60598-2 part 5, which allows them to be classified as illumination projectors. This means complete freedom of installation in any position, with 360° rotation and resistance to strong winds – an advantage not offered by other floodlights. An additional advantage for contractors is the sealed quick connector – an innovative solution that eliminates traditional, time-consuming connection methods (screws). Thanks to an intuitive system of coloured latches, connector installation is simple, quick and tool-free. The accessory kit includes: pole mounting brackets (basic version); frame for flush mounting, e.g. in shelters (basic version); light pollution reduction screens (basic version); protective grids in two colours with different degrees of light reduction (white RAL7016: 4%, body colour RAL7016: 8%).

APPLICATION

Quest LED Evo XS Endura and Quest LED Evo XS Endura HB NT are used in: lighting educational, administrative and institutional facilities, halls, garages, passageways, warehouses, shops, the food industry and commercial and service facilities related to food products. Illumination of buildings, small sports fields, open spaces and car parks, environments with elevated ambient temperatures (up to 50 degrees C). Installation options: as a floodlight, on poles and masts, on building facades, as a surface-mounted highbay (HB NT version), suspended highbay (HB Z version), flush-mounted (e.g. shelters). The product is particularly well suited for use in factories and production halls as well as large-area warehouses, especially in areas exposed to high temperatures.



QUEST LED EVO XS ENDURA HBZ 6000LM I CL. IP67 840 CN (33X68D) 41W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	798559
EAN:	5905963798559
Light source:	LED
Rated power of the luminaire [W]:	41
Supply voltage [V]:	220-240
Frequency [Hz]:	50/60
Luminous flux [Im]:	6000
Luminous efficacy [lm/W]:	146
Energy efficiency class:	С
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Beam angle [°]:	33 x 68
Surge protection [kV]:	6
Diffuser material:	glass
Diffuser type:	transparent
Material of the body:	aluminium
Colour of the body:	RAL7016
Dimensions (H/W/T/S) [mm]:	280/240/55 (390/310/325)
Mounting dimensions [mm]:	265/45

Ingress protection: Mounting version: Working temperature [°C]: Number on the palette [pcs]: Net weight [kg]: Category type: AC voltage range [V]: Version: Light distribution type: LED lifespan L70B50 [h]: LED lifespan L90B10 [h]: LED lifespan L90B10 [h]: Category of application: Warranty [years]: CE certificate: Environmental Product Declaration (EPD): suspended 103000	Impact resistance:	IK10
Working temperature [°C]: Number on the palette [pcs]: 45 Net weight [kg]: 2.900 Category type: floodlights AC voltage range [V]: 100-305 Version: HB suspended Light distribution type: CN LED lifespan L70B50 [h]: 165000 LED lifespan L80B20 [h]: 103000 LED lifespan L90B10 [h]: 48000 Corrosivity category: C5-M Category of application: industrial Warranty [years]: CE certificate: Environmental Product Declaration (EPD): 816/2025	Ingress protection:	IP67
Number on the palette [pcs]: 45 Net weight [kg]: 2.900 Category type: floodlights AC voltage range [V]: 100-305 Version: HB suspended Light distribution type: CN LED lifespan L70B50 [h]: 165000 LED lifespan L80B20 [h]: 103000 LED lifespan L90B10 [h]: 48000 Corrosivity category: C5-M Category of application: industrial Warranty [years]: 5 CE certificate: 02/2025 Environmental Product Declaration (EPD): 816/2025	Mounting version:	suspended
Net weight [kg]: 2.900 Category type: floodlights AC voltage range [V]: 100-305 Version: HB suspended Light distribution type: CN LED lifespan L70B50 [h]: 165000 LED lifespan L80B20 [h]: 103000 LED lifespan L90B10 [h]: 48000 Corrosivity category: C5-M Category of application: industrial Warranty [years]: 5 CE certificate: 02/2025 Environmental Product Declaration (EPD): 816/2025	Working temperature [°C]:	from -20 to +50
Category type: AC voltage range [V]: Version: Light distribution type: LED lifespan L70B50 [h]: LED lifespan L80B20 [h]: LED lifespan L90B10 [h]: Corrosivity category: Category of application: Warranty [years]: CE certificate: Environmental Product Declaration (EPD): 100-305 HB suspended 103-00 L8000 CN L8000 CN L8000 CN L8000 CS-M industrial 5 CE certificate: 02/2025 Environmental Product Declaration (EPD):	Number on the palette [pcs]:	45
AC voltage range [V]: Version: Light distribution type: LED lifespan L70B50 [h]: LED lifespan L80B20 [h]: LED lifespan L90B10 [h]: Corrosivity category: Category of application: Warranty [years]: CE certificate: Environmental Product Declaration (EPD): 100-305 HB suspended 48 uspended 165000 16	Net weight [kg]:	2.900
Version: Light distribution type: CN LED lifespan L70B50 [h]: LED lifespan L80B20 [h]: LED lifespan L90B10 [h]: 48000 Corrosivity category: C5-M Category of application: industrial Warranty [years]: CE certificate: Environmental Product Declaration (EPD): HB suspended 165000 16500	Category type:	floodlights
Light distribution type: LED lifespan L70B50 [h]: LED lifespan L80B20 [h]: LED lifespan L90B10 [h]: Corrosivity category: C5-M Category of application: Warranty [years]: CE certificate: Environmental Product Declaration (EPD): S165000 103000 48000 C5-M industrial 5 CE certificate: 92/2025 Environmental Product Declaration (EPD):	AC voltage range [V]:	100-305
LED lifespan L70B50 [h]: LED lifespan L80B20 [h]: LED lifespan L90B10 [h]: Corrosivity category: C5-M Category of application: Warranty [years]: CE certificate: Environmental Product Declaration (EPD): 165000 103000 103000 1048000 1050000 105000 105000 1050000 1050000 1050000 1050000 1050000 1050	Version:	HB suspended
LED lifespan L80B20 [h]: 103000 LED lifespan L90B10 [h]: 48000 Corrosivity category: C5-M Category of application: industrial Warranty [years]: 5 CE certificate: 02/2025 Environmental Product Declaration (EPD): 816/2025	Light distribution type:	CN
LED lifespan L90B10 [h]: Corrosivity category: C5-M Category of application: Warranty [years]: CE certificate: Environmental Product Declaration (EPD): 816/2025	LED lifespan L70B50 [h]:	165000
Corrosivity category: Category of application: Warranty [years]: CE certificate: Environmental Product Declaration (EPD): 816/2025	LED lifespan L80B20 [h]:	103000
Category of application: industrial Warranty [years]: 5 CE certificate: 02/2025 Environmental Product Declaration (EPD): 816/2025	LED lifespan L90B10 [h]:	48000
Warranty [years]: 5 CE certificate: 02/2025 Environmental Product Declaration (EPD): 816/2025	Corrosivity category:	C5-M
CE certificate: 02/2025 Environmental Product Declaration (EPD): 816/2025	Category of application:	industrial
Environmental Product Declaration (EPD): 816/2025	Warranty [years]:	5
· · ——	CE certificate:	02/2025
Manual: Download PDF	Environmental Product Declaration (EPD):	816/2025
	Manual:	Download PDF
Plik LDT: <u>Download</u>	Plik LDT:	Download




QUEST LED EVO XS ENDURA HBZ 6000LM I CL. IP67 840 CN (33X68D) 41W


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WSEL438	Remote control for motion sensor HD01R
840456	QUEST LED EVO XS recessed frame RAL7016







QUEST LED EVO XS recessed frame RAL7016 (840456)

