

POINT LED 8W SZKŁO PRM 3000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	225130
Ingress protection:	IP44
Impact resistance:	IK07
Nominal power [W]:	8
Luminous flux [lm]*:	850
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	glass

CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, ingress protection class IP44 and an integrated energy-saving light source LED GO!. White base made of polypropylene; opal or prismatic glass diffuser. Available with a radio motion sensor (RCR). Color temperature 3000K/4000K, CRI>80, lifespan of LED 50 000h (L70B50) ta= 25 °C.

APPLICATION

surface mounted luminaire for mounting on ceilings and walls; intended both for indoor (maintenance rooms, passageways) and outdoor use (façade lighting). The version with a radio motion sensor (RCR) is particularly well-suited to be used as a light source for public rooms and buildings (civic buildings, apartment buildings).

POINT LED 8W SZKŁO PRM 3000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	8	Colour of the body:	white
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø230/90
Colour temperature [K]:	3000	Impact resistance:	IK07
Luminous flux [lm]:	850	Ingress protection:	IP44
Rated power of the luminaire [W]:	8	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Diffuser type:	PRM	Net weight [kg]:	1
Frequency [Hz]:	50 - 60	Warranty [years]:	5
Energy efficiency class:	E	Index:	225130
Luminous efficacy [lm/W]:	106	CE certificate:	403/2023
Electrical protection class:	I	EAN:	5905963225130
Colour rendering index:	>80	Category type:	bulkheads
SDCM:	≤ 3	ETIM class:	EC002892
LED lifespan L70B50 [h]:	50000	Category of application:	parkings and bicycle paths
Beam angle [°]:	120	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	glass	Manual:	Download PDF
Material of the body:	PP	Plik LDT:	

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 403/2023