

GAMMA LED 280 2600LM 840 IP54 II CL. RCR OPAL (20W) 280MM (HYTRONIK)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	192173
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	20
Luminous flux [lm]*:	2600
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

The latest version of the popular plafond - even better performance, same proven quality.

Surface-mounted, round LED light fitting with a luminous flux of 87 lm/W, ingress protection class IP54 and an integrated energy-saving light source LED. White base; diffuser made of impact-resistant PC provides even light distribution and ensures a high impact resistance class (IK10).

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.


GAMMA LED 280 2600LM 840 IP54 II CL. RCR OPAL (20W) 280MM (HYTRONIK)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	192173	Optics material:	PC
EAN:	5905963192173	Material of the body:	PP
Light source:	LED module	Colour of the body:	white
Nominal power [W]:	20	Dimensions (H/W/T/S) [mm]:	ø280/72
Rated power of the luminaire [W]:	20	Mounting dimensions [mm]:	160
Supply voltage [V]:	220-240	Impact resistance:	IK10
Luminous flux [lm]:	2600	Ingress protection:	IP54
Luminous efficacy [lm/W]:	130	Mounting version:	surface
Energy efficiency class:	E	Working temperature [°C]:	from -20 to +25
Electrical protection class:	II	Motion sensor:	yes
Colour temperature [K]:	4000	Dimensions of single box [mm]:	280
Color rendering index (Ra) >:	80	Net weight [kg]:	0.430
SDCM:	3	Category type:	bulkheads
Power factor:	0.90	Version:	RCR Hytronik
LED lifespan L70B50 [h]:	119000	Light distribution type:	open space
Beam angle [°]:	120	Warranty [years]:	5
Surge protection [kV]:	1	CE certificate:	392/2023
Diffuser material:	PC	PZH certificate:	
Diffuser type:	OPAL	Manual:	Download PDF
Diffuser colour:	white	Pliik LDT:	Download

LIGHT CURVES




GAMMA LED 280 2600LM 840 IP54 II CL. RCR OPAL (20W) 280MM (HYTRONIK)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WSE0005	RC MOS MR004 IoT programming remote control



RC MOS MR004 IoT programming
remote control (WSE0005)

Card creation date: 02 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 392/2023