LUMEDIC 595X595MM SM 9600LM 840 GLASS/OPAL/PRM MB IP65/50 I CL. W IK09 86W

DETAILED CARD





TECHNICAL PARAMETERS

Index: 783043

Ingress protection: IP65/50

Impact resistance: IK09

Rated power of the luminaire [W]*: 86

Luminous flux [lm]*: 9600

Colour temperature [K]: 4000

Colour rendering index: 80

Energy efficiency class:

Material of the body: powder coated steel

Diffuser material: szyba hartowana

CHARACTERISTICS

Lumedic is a specialist Cleanroom luminaire designed for clean rooms with increased hygiene and sterility requirements. Its design ensures ease of cleaning and high mechanical and environmental resistance. A robust steel housing with IP65 protection on the room side and IP50 on the technical side ensures complete tightness in a sterile environment, while allowing free air flow above the suspended ceiling. Service access is provided from the technical side (top inspection), allowing maintenance without interfering with the clean room.

The front of the luminaire is made of aluminium and 4 mm thick tempered glass, resistant to impact (IK09 class) and chemicals. The modular shutter system (Glass / Opal / PRM) allows you to select the appropriate optical characteristics depending on the application requirements — from uniform, diffused light to precise directional distribution.

APPLICATION

- $\bullet \ \ laboratories \ (microbiological, \ pharmaceutical, \ chemical),$
- hospitals (operating theatres, intensive care units, diagnostic laboratories),
- food and pharmaceutical industry,
- cleanrooms in electronics and semiconductor manufacturing.



LUMEDIC 595X595MM SM 9600LM 840 GLASS/OPAL/PRM MB IP65/50 I CL. W IK09 86W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	783043
EAN:	5905963783043
Light source:	LED module
Rated power of the luminaire [W]:	86
Supply voltage [V]:	220 - 240
Frequency [Hz]:	0-50-60
Luminous flux [Im]:	9600
Luminous efficacy [lm/W]:	112
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	4000
Colour rendering index:	80
Power factor:	0.95
Surge protection [kV]:	2
Diffuser material:	szyba hartowana
Diffuser type:	Opal PRM
Optics material:	PC
Optics:	PRM
Material of the body:	powder coated steel

Colour of the body:	white Ral9003
Ring colour:	white Ral9003
Dimensions (H/W/T/S) [mm]:	595/595/65
Mounting dimensions [mm]:	585/585
Impact resistance:	IK09
Ingress protection:	IP65/50
Mounting version:	recessed
Working temperature [°C]:	from -20 to +35
Number on the palette [pcs]:	16
Net weight [kg]:	11
SDCM:	3
LED lifespan L70B50 [h]:	149000
LED lifespan L80B20 [h]:	100000
LED lifespan L90B10 [h]:	50000
Warranty [years]:	5
CE certificate:	123/2025
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 08 October 2025



