## BARIS 40 LED UGR PLUS N IOT BT PIR HYT DALI MASTER 3725LM I CL. IP20 1421MM 830 31W BLACK 70D

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index:	939563
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	31
Luminous flux [lm]*:	3725
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	black

#### **CHARACTERISTICS**

The BARIS 40 LED UGR PLUS IoT luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver.

The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

loT

characteristics

**IOT BT PIR HYT DALI: HYT Bluetooth** module controlled in the Lena Lighting Clue app, **PIR** motion and light sensor, **DALI** driver allowing dimming of the light source.

#### **APPLICATION**

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.



# BARIS 40 LED UGR PLUS N IOT BT PIR HYT DALI MASTER 3725LM I CL. IP20 1421MM 830 31W BLACK 70D

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	939563
EAN:	5905963939563
Light source:	LED
Rated power of the luminaire [W]:	31
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	3725
Luminous efficacy [lm/W]:	120
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	80
SDCM:	3
Power factor:	0.97
LED lifespan L70B50 [h]:	153000
LED lifespan L80B20 [h]:	96000
LED lifespan L90B10 [h]:	46000
Beam angle [°]:	70
Optics material:	PC
Optics:	lens
Material of the body:	aluminium

Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	53/40/1461
Mounting dimensions [mm]:	1310
Impact resistance:	IK03
Ingress protection:	IP20
Mounting version:	surface
Working temperature [°C]:	35
PIR:	yes
DIMM DALI:	yes
Control:	yes
Master/slave:	master
Number on the palette [pcs]:	40
Net weight [kg]:	1.609
Category type:	luminaires and linear systems
Category of application:	office lighting
Version:	BT PIR HYT DALI
Warranty [years]:	5
CE certificate:	133/2025
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 21 October 2025



