


# BARIS 40 LED UGR PLUS N IOT BT PIR HYT DALI MASTER 2850LM I CL. IP20 1140MM 830 24W BLACK 70D

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	939808
<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK03
<b>Rated power of the luminaire [W]*:</b>	24
<b>Luminous flux [lm]*:</b>	2850
<b>Colour temperature [K]:</b>	3000
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black

## CHARACTERISTICS

The BARIS 40 LED UGR PLUS IoT luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver.

The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

### IoT characteristics

**IoT BT PIR HYT DALI:** HYT Bluetooth module controlled in the Lena Lighting Clue app, PIR motion and light sensor, DALI driver allowing dimming of the light source.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

# BARIS 40 LED UGR PLUS N IOT BT PIR HYT DALI MASTER 2850LM I CL. IP20 1140MM 830 24W BLACK 70D

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	939808	Colour of the body:	black
EAN:	5905963939808	Dimensions (H/W/T/S) [mm]:	53/40/1180
Light source:	LED	Mounting dimensions [mm]:	1030
Rated power of the luminaire [W]:	24	Impact resistance:	IK03
Supply voltage [V]:	220 - 240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	2850	Working temperature [°C]:	35
Luminous efficacy [lm/W]:	119	PIR:	yes
Energy efficiency class:	D	DIMM DALI:	yes
Electrical protection class:	I	Control:	yes
Colour temperature [K]:	3000	Master/slave:	master
Color rendering index (Ra) >:	80	Number on the palette [pcs]:	40
SDCM:	3	Net weight [kg]:	1.409
Power factor:	0.96	Category type:	luminaires and linear systems
LED lifespan L70B50 [h]:	153000	Category of application:	office lighting
LED lifespan L80B10 [h]:	96000	Version:	BT PIR HYT DALI
LED lifespan L90B10 [h]:	46000	Warranty [years]:	5
Beam angle [°]:	70	CE certificate:	<a href="#">133/2025</a>
Optics material:	PC	Manual:	<a href="#">Download PDF</a>
Optics:	lens	Plik LDT:	<a href="#">Download</a>
Material of the body:	aluminium		

Card creation date: 21 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 133/2025