

# ASTRA S LED PRO 2050LM 830 AR5 IP66 II CL. DALI WIRE 0,7M PLUG/GN SP1KV 12W (N)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	782060
<b>Ingress protection:</b>	IP66
<b>Rated power of the luminaire [W]*:</b>	12
<b>Luminous flux [lm]*:</b>	2050
<b>Colour temperature [K]:</b>	3000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Electrical protection class:</b>	II
<b>Optics:</b>	AR5
<b>Colour of the body:</b>	grey
<b>Luminous efficacy [lm/W]:</b>	171

## CHARACTERISTICS

LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

## APPLICATION

Road luminaire suitable for illumination of: streets and municipal, local, internal and neighbourhood roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.

# ASTRA S LED PRO 2050LM 830 AR5 IP66 II CL. DALI WIRE 0,7M PLUG/GN SP1KV 12W (N)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	782060	Diffuser material:	PC
EAN:	5905963782060	Optics material:	PC
Category type:	street lighting	Optics:	AR5
Light source:	LED module	Colour of the body:	grey
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	75/175/500
Supply voltage [V]:	220 - 240	Ingress protection:	IP66
Frequency [Hz]:	50 - 60	Cable length [m]:	0.70
Luminous flux [lm]:	2050	Product line:	PRO
Luminous efficacy [lm/W]:	171	Impact resistance:	IK08
Energy efficiency class:	B	DIMM DALI:	yes
Electrical protection class:	II	Warranty [years]:	5
Colour temperature [K]:	3000	CE certificate:	<a href="#">42/2024</a>
Color rendering index (Ra) >:	80	ENEC Certificate:	<a href="#">0373/ENEC/24</a>
SDCM:	3	Manual:	<a href="#">Download PDF</a>
Power factor:	0.82	Category of application:	Street lighting
Surge protection [kV]:	1	Pliik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# ASTRA S LED PRO 2050LM 830 AR5 IP66 II CL. DALI WIRE 0,7M PLUG/GN SP1KV 12W (N)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
598357	Pole adapter 80/60 ALU
UL00214	Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED



Pole adapter 80/60 ALU (598357)



Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED (UL00214)

Card creation date: 22 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 42/2024