

BARIS 52 LED UGR PLUS Z 1423MM 4475LM 840 IP20 I CL. DALI BLACK 33W SINGLE 70D

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-----------|
| Index: | 121715 |
| Ingress protection: | IP20 |
| Impact resistance: | IK06 |
| Rated power of the luminaire [W]*: | 33 |
| Luminous flux [lm]*: | 4475 |
| Colour temperature [K]: | 4000 |
| Color rendering index (Ra) >: | 80 |
| SDCM: | 3 |
| Energy efficiency class: | D |
| Material of the body: | aluminium |

CHARACTERISTICS

Baris 52 LED UGR Plus Single is a modern LED linear luminaire designed for demanding office, commercial and architectural spaces. Its minimalist design, slim form and perfectly refined optics make it a perfect fit for any contemporary interior – from elegant open-plan offices to modern conference rooms, reception areas and co-working spaces. The luminaire combines the highest quality of light with above-average efficiency. With an efficiency of up to 154 lm/W, it provides uniform, comfortable lighting with low energy consumption. Specially designed UGR<19 optics guarantee high visual comfort by eliminating annoying glare – particularly important in workplaces with computer screens. The availability of two lengths and two mounting options – surface-mounted and suspended – allows for complete freedom of arrangement and adaptation of the luminaire to the character of the interior. The aluminium body, available in three elegant colours (grey, white and black), emphasises the modern, timeless style of the product. The luminaire also offers a wide range of control options, including a DALI version, which facilitates integration with advanced lighting management systems. It is an excellent choice wherever quality, aesthetics and functionality are important – in one perfectly designed form.

APPLICATION

The luminaire is designed for indoor use. It is used as a main light source and is ideal for office work requiring visual concentration. Its unique design, energy-efficient LED modules and compatibility with external DALI lighting control systems make it ideal for use in modern A+ class office buildings, particularly in representative rooms.

BARIS 52 LED UGR PLUS Z 1423MM 4475LM 840 IP20 I CL. DALI BLACK 33W SINGLE 70D

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|---|------------------------------|
| Index: | 121715 | Optics: | lens |
| EAN: | 5905963121715 | Material of the body: | aluminium |
| Light source: | LED module | Colour of the body: | black |
| Rated power of the luminaire [W]: | 33 | Dimensions (H/W/T/S) [mm]: | 69/52/1423 |
| Supply voltage [V]: | 220 - 240 | Mounting dimensions [mm]: | 1315 |
| Frequency [Hz]: | 50 - 60 | Impact resistance: | IK06 |
| Luminous flux [lm]: | 4475 | Ingress protection: | IP20 |
| Luminous efficacy [lm/W]: | 136 | Mounting version: | suspended |
| Energy efficiency class: | D | Working temperature [°C]: | 35 |
| Electrical protection class: | I | DIMM DALI: | yes |
| Colour temperature [K]: | 4000 | Number on the palette [pcs]: | 40 |
| Color rendering index (Ra) >: | 80 | Net weight [kg]: | 2.143 |
| SDCM: | 3 | UGR (4H8H): | <19 |
| Power factor: | 0.97 | Warranty [years]: | 5 |
| LED lifespan L70B50 [h]: | 153000 | CE certificate: | 145/2025 |
| LED lifespan L80B10 [h]: | 96000 | Manual: | Download PDF |
| LED lifespan L90B10 [h]: | 46000 | Environmental Product Declaration (EPD): | 852/2025 |
| Beam angle [°]: | 70 | Plik LDT: | Download |
| Optics material: | PC | | |

Card creation date: 04 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 145/2025