

ELEGANTE LED 1136MM 2400LM OPAL IP44 830 (30W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|-----------|
| Ingress protection: | IP44/20 |
| Impact resistance: | IK02 |
| Nominal power [W]: | 30 |
| Luminous flux [lm]*: | 2400 |
| Colour temperature [K]: | 3000 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | G |
| Material of the body: | aluminium |
| Colour of the body: | silver |
| Diffuser material: | PC |

CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution.

APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.


ELEGANTE LED 1136MM 2400LM OPAL IP44 830 (30W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|----------------------------|----------------------------|
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | 1136/52/66 |
| Nominal power [W]: | 30 | Mounting dimensions [mm]: | 1139/54 |
| Rated power of the luminaire [W]: | 33.50 | Impact resistance: | IK02 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP44/20 |
| Frequency [Hz]: | 50 - 60 | Mounting version: | recessed |
| Luminous flux [lm]: | 2400 | Working temperature [°C]: | from -17 to +35 |
| Luminous efficacy [lm/W]: | 71 | Accessories included: | diffuser |
| Energy efficiency class: | G | Net weight [kg]: | 2.200 |
| Electrical protection class: | I | CE certificate: | 243/2023 |
| Colour temperature [K]: | 3000 | Index: | 388583 |
| Colour rendering index: | >80 | EAN: | 5905963388583 |
| SDCM: | ≤ 3 | Category type: | systems |
| LED lifespan L70B50 [h]: | 115000 | Version: | individual |
| Diffuser material: | PC | Product line: | INDIVIDUAL VARIANT 30W/15W |
| Diffuser type: | OPAL | Light distribution type: | open space |
| Diffuser colour: | white | | |
| Material of the body: | aluminium | | |
| Colour of the body: | silver | | |

LIGHT CURVES



ELEGANTE LED 1136MM 2400LM OPAL IP44 830 (30W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|----------|---|
| 81000945 | ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm) |
| 388736 | ELEGANTE SYSTEM LED end set |
| 388743 | ELEGANTE SYSTEM LED gniazdo 3 polowe |
| 388750 | ELEGANTE SYSTEM LED gniazdo 5 polowe |
| 388767 | ELEGANTE SYSTEM LED wtyk 3 polowy |
| 388774 | ELEGANTE SYSTEM LED wtyk 5 polowy |
| 388729 | ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m |



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 22 August 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 243/2023