GAMMA LED BASIC 280 1240LM 840 IP54 II CL. SIDE PIR OPAL (10W) 280MM + REMOTE CONTROL

DETAILED CARD



TECHNICAL PARAMETERS

Index:	192289
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	10
Luminous flux [lm]*:	1240
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	D
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

The latest version of our bestseller - even better performance, same proven quality.
Surface-mounted, round LED light fitting, ingress protection class IP54, and an integrated energy-saving light source LED. White base; diffuser made of impact-resistant PC provides even light distribution and ensures a high impact resistance class (IK10).

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.
The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.


GAMMA LED BASIC 280 1240LM 840 IP54 II CL. SIDE PIR OPAL (10W) 280MM + REMOTE CONTROL

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	192289	**Colour of the body:**	white
EAN:	5905963192289	**Dimensions (H/W/T/S) [mm]:**	ø280/72
Light source:	LED module	**Mounting dimensions [mm]:**	160
Nominal power [W]:	10	**Impact resistance:**	IK10
Rated power of the luminaire [W]:	10	**Ingress protection:**	IP54
Supply voltage [V]:	220-240	**Mounting version:**	surface
Luminous flux [lm]:	1240	**Working temperature [°C]:**	from -20 to +25
Luminous efficacy [lm/W]:	124	**Dimensions of single box [mm]:**	280
Energy efficiency class:	D	**Number on the palette [pcs]:**	80
Electrical protection class:	II	**Net weight [kg]:**	0.430
Colour temperature [K]:	4000	**Category type:**	bulkheads
Color rendering index (Ra) >:	80	**Light distribution type:**	open space
SDCM:	3	**PIR:**	yes
Power factor:	0.55	**LED lifespan L80B10 [h]:**	79500
LED lifespan L70B50 [h]:	125000	**LED lifespan L90B10 [h]:**	38500
Beam angle [°]:	120	**Accessories included:**	Remote control
Surge protection [kV]:	1	**Warranty [years]:**	5
Diffuser material:	PC	**CE certificate:**	48/2025
Diffuser type:	OPAL	**PZH certificate:**	B-BK-60112-0232/2025
Diffuser colour:	white	**Environmental Product Declaration (EPD):**	944/2026
Optics material:	PC	**Manual:**	Download PDF
Material of the body:	PP	**ISO Certificates:**	9001:2015. 14001:2015, 45001:2018, 50001:2018

LIGHT CURVES




GAMMA LED BASIC 280 1240LM 840 IP54 II CL. SIDE PIR OPAL (10W) 280MM + REMOTE CONTROL

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WSE0005	RC MOS MR004 IoT programming remote control



RC MOS MR004 IoT programming remote control (WSE0005)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 48/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl