LINERO LED 632MM 15650LM 840 IP66 SW 111W

DETAILED CARD





TECHNICAL PARAMETERS

Index: 488108 Ingress protection: IP66 Rated power of the luminaire [W]*: 111 Luminous flux [lm]*: 15650 Colour temperature [K]: 4000 Color rendering index (Ra) >: 80 **Electrical protection class:** С **Energy efficiency class:** Material of the body: aluminium

Mounting version: surface, suspended

CHARACTERISTICS

A family of lightweight, linear, high-bay, hermetic luminaires made of extruded aluminium, with a heat sink to dissipate excess heat and a separate compartment for the power supply. It combines durability and tightness with maximum light efficiency. Its uncompromising, modern design represents a breakthrough in the design of efficient and economical industrial luminaires. The modular construction allows for maximum light output at low cost and size. Professional optics made of durable polycarbonate (PC) provide great freedom in choosing the optimal solution, even at significant mounting heights.

APPLICATION

Designed for the most demanding production and warehouse spaces.



LINERO LED 632MM 15650LM 840 IP66 SW 111W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	488108
EAN:	5905963488108
Light source:	LED module
Rated power of the luminaire [W]:	111
Luminous flux [Im]:	15650
Supply voltage [V]:	220-240
Luminous efficacy [lm/W]:	141
Energy efficiency class:	С
Electrical protection class:	Ш
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Material of the body:	aluminium

Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	632/61/129
Mounting dimensions [mm]:	129
Ingress protection:	IP66
Mounting version:	surface, suspended
Working temperature [°C]:	35
Dimensions of single box [mm]:	188/89/293
Light distribution type:	SW
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	<u>152/2025</u>
Manual:	Download PDF

Card creation date: 12 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



