

# LINERO LED 632MM 14450LM 840 IP66 VW 99W

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |                    |
|------------------------------------|--------------------|
| Index:                             | 488177             |
| Ingress protection:                | IP66               |
| Rated power of the luminaire [W]*: | 99                 |
| Luminous flux [lm]*:               | 14450              |
| Colour temperature [K]:            | 4000               |
| Color rendering index (Ra) >:      | 80                 |
| Electrical protection class:       | II                 |
| Energy efficiency class:           | C                  |
| Material of the body:              | aluminium          |
| Mounting version:                  | surface, suspended |

## CHARACTERISTICS

A family of lightweight, linear, high-bay, hermetic luminaires made of extruded aluminium, with a heat sink to dissipate excess heat and a separate compartment for the power supply. It combines durability and tightness with maximum light efficiency. Its uncompromising, modern design represents a breakthrough in the design of efficient and economical industrial luminaires. The modular construction allows for maximum light output at low cost and size. Professional optics made of durable polycarbonate (PC) provide great freedom in choosing the optimal solution, even at significant mounting heights.

## APPLICATION

Designed for the most demanding production and warehouse spaces.

# LINERO LED 632MM 14450LM 840 IP66 VW 99W

DETAILED CARD


## TECHNICAL PARAMETERS TABLE

|                                   |               |                                |   |
|-----------------------------------|---------------|--------------------------------|---|
| Index:                            | 488177        | Colour of the body:            | black   |
| EAN:                              | 5905963488177 | Dimensions (H/W/T/S) [mm]:     | 632/61/129  |
| Light source:                     | LED module    | Mounting dimensions [mm]:      | 129   |
| Rated power of the luminaire [W]: | 99            | Ingress protection:            | IP66  |
| Luminous flux [lm]:               | 14450         | Mounting version:              | surface, suspended  |
| Supply voltage [V]:               | 220-240       | Working temperature [°C]:      | 35  |
| Luminous efficacy [lm/W]:         | 146           | Dimensions of single box [mm]: | 188/89/293  |
| Energy efficiency class:          | C             | Light distribution type:       | VW  |
| Electrical protection class:      | II            | Photobiological safety:        | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour temperature [K]:           | 4000          | Warranty [years]:              | 5   |
| Color rendering index (Ra) >:     | 80            | CE certificate:                | <a href="#">152/2025</a>  |
| Material of the body:             | aluminium     | Manual:                        | <a href="#">Download PDF</a>  |

Card creation date: 12 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 152/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)