

LINERO LED 632MM 11000LM 840 IP66 VN 71W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	488252
Ingress protection:	IP66
Rated power of the luminaire [W]*:	71
Luminous flux [lm]*:	11000
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	II
Energy efficiency class:	C
Material of the body:	aluminium
Mounting version:	surface, suspended

CHARACTERISTICS

A family of lightweight, linear, high-bay, hermetic luminaires made of extruded aluminium, with a heat sink to dissipate excess heat and a separate compartment for the power supply. It combines durability and tightness with maximum light efficiency. Its uncompromising, modern design represents a breakthrough in the design of efficient and economical industrial luminaires. The modular construction allows for maximum light output at low cost and size. Professional optics made of durable polycarbonate (PC) provide great freedom in choosing the optimal solution, even at significant mounting heights.

APPLICATION

Designed for the most demanding production and warehouse spaces.

LINERO LED 632MM 11000LM 840 IP66 VN 71W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	488252	Dimensions (H/W/T/S) [mm]:	632/61/129
EAN:	5905963488252	Mounting dimensions [mm]:	129
Light source:	LED module	Ingress protection:	IP66
Rated power of the luminaire [W]:	71	Mounting version:	surface, suspended
Luminous flux [lm]:	11000	Working temperature [°C]:	35
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	188/89/293
Luminous efficacy [lm/W]:	155	Light distribution type:	VN
Energy efficiency class:	C	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Electrical protection class:	II	Warranty [years]:	5
Colour temperature [K]:	4000	CE certificate:	152/2025
Color rendering index (Ra) >:	80	Manual:	Download PDF
Material of the body:	aluminium	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Colour of the body:	black		

Card creation date: 12 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 152/2025