

EXPO MODULAR TRACK 3250LM DALI 60D WHITE MATT TEXTURE 940 35W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	236624
Ingress protection:	IP20
Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	3100
Colour temperature [K]:	3000
Color rendering index (Ra) >:	90
Material of the body:	aluminium
Colour of the body:	white
Optics:	reflector
Beam angle [°]:	60

CHARACTERISTICS

EXPO Modular is a projector luminaire developed from scratch, which opens up a range of new functionalities for the user. Low UGR glare effect, precise optics, high CRI, the possibility of expanding the luminaire's functionality or giving it an individual character through a wide range of accessories such as ecoPET screens or accessories such as unusual shades, screens and covers made with 3D printing. The luminaire's design ensures optimal thermal performance and allows for changing the lighting angles, as well as customising the colour of the ring and body. EXPO Modular is a high-quality aluminium projector with a COB LED light source. Universal application with a busbar system. No ultraviolet or infrared radiation, high colour rendering index, high luminous efficacy and high durability.

APPLICATION

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

EXPO MODULAR TRACK 3250LM DALI 60D WHITE MATT TEXTURE 940 35W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	236624	Colour of the body:	white
EAN:	5905963236624	Ring material:	aluminium
Light source:	COB	Ring colour:	white
Rated power of the luminaire [W]:	35	Dimensions (H/W/T/S) [mm]:	fi=80 L=215
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	track
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	3100	Mounting version:	track
Luminous efficacy [lm/W]:	89	DIMM DALI:	yes
Energy efficiency class:	F	Dimensions of single box [mm]:	245/230/90
Electrical protection class:	II	Number on the palette [pcs]:	165
Colour temperature [K]:	3000	Net weight [kg]:	0.850
Color rendering index (Ra) >:	90	Gross weight [kg]:	0.970
Beam angle [°]:	60	LED lifespan L90B10 [h]:	50000
Exchangeable source:	yes	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	156/2025
Material of the body:	aluminium	Manual:	Download PDF