

TYTAN STEEL LED RAPID 600MM 2300LM 840 IP66 120D 14W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	189135
Ingress protection:	IP66
Impact resistance:	IK06
Rated power of the luminaire [W]*:	14
Luminous flux [lm]*:	2300
Colour temperature [K]:	4000
Material of the body:	coated steel
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

Tytan Steel LED Rapid reflects an innovative approach to classic hermetic luminaires, combining functionality with aesthetics. All the technical advantages of traditional hermetic luminaires have been enclosed in an elegant, low profile, giving the lamp a modern design. Thanks to its advanced optics, Tytan Steel LED Rapid is suitable for both the simplest applications and demanding industrial solutions. The product is exceptionally easy to install and has low purchase and operating costs (169 lm/W).

The **RAPID** designation indicates even faster installation (compared to classic, openable hermetic luminaires) thanks to a 0.6 m long cable leading directly from the luminaire and terminated with a sealed quick connector. This allows the power supply to be connected without opening the lamp. At the same time, the luminaire can still be opened for servicing. Through-wired versions have two cables of the same design. The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED Rapid lamp is made of steel, which ensures its exceptional durability, and thanks to its U-shaped profile design, it retains the lightness characteristic of plastic luminaires, which facilitates installation and does not burden the supporting structures.

Tytan Steel LED Rapid is an optimal combination of functionality and economy, ideal for a wide range of applications.

APPLICATION

The multi-purpose LED lamp is designed for use in areas with high dust and water resistance requirements. It is particularly recommended for lighting industrial and warehouse halls, garages, car parks (underground and multi-storey), public facilities, including hospitals, educational and childcare facilities, commercial and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as for replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.

TYTAN STEEL LED RAPID 600MM 2300LM 840 IP66 120D 14W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	189135	Diffuser type:	matrix led
EAN:	5905963189135	Material of the body:	coated steel
Light source:	LED module	Colour of the body:	white
Rated power of the luminaire [W]:	14	Dimensions (H/W/T/S) [mm]:	600/57/45
Luminous flux [lm]:	2300	Mounting dimensions [mm]:	520
Supply voltage [V]:	220-240	Impact resistance:	IK06
Frequency [Hz]:	50-60	Ingress protection:	IP66
Luminous efficacy [lm/W]:	164	Mounting version:	surface, suspended
Energy efficiency class:	B	Working temperature [°C]:	from +35 to -20
Electrical protection class:	I	Number on the palette [pcs]:	110
Colour temperature [K]:	4000	Net weight [kg]:	0.850
Color rendering index (Ra) >:	80	Light distribution type:	symmetric
SDCM:	3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	140000	Warranty [years]:	5
LED lifespan L80B10 [h]:	88000	CE certificate:	159/2025
LED lifespan L90B10 [h]:	42000	Manual:	Download PDF
Beam angle [°]:	120	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Surge protection [kV]:	2	Plik LDT:	Download
Diffuser material:	PC		

Card creation date: 24 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 159/2025